

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
BM-236
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a components first oil change.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0113986	---	---
Sample Date	Client Info		12 Jun 2024	---	---
Machine Age	mls	Client Info	34877	---	---
Oil Age	mls	Client Info	34877	---	---
Oil Changed	Client Info		Changed	---	---
Sample Status			NORMAL	---	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	---	---
Water	WC Method	>0.2	NEG	---	---
Glycol	WC Method		NEG	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	89	---
Chromium	ppm	ASTM D5185m	>20	2	---
Nickel	ppm	ASTM D5185m	>4	1	---
Titanium	ppm	ASTM D5185m		1	---
Silver	ppm	ASTM D5185m	>3	1	---
Aluminum	ppm	ASTM D5185m	>20	77	---
Lead	ppm	ASTM D5185m	>40	<1	---
Copper	ppm	ASTM D5185m	>330	23	---
Tin	ppm	ASTM D5185m	>15	2	---
Vanadium	ppm	ASTM D5185m		<1	---
Cadmium	ppm	ASTM D5185m		<1	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	15	---
Barium	ppm	ASTM D5185m	0	0	---
Molybdenum	ppm	ASTM D5185m	50	21	---
Manganese	ppm	ASTM D5185m	0	3	---
Magnesium	ppm	ASTM D5185m	950	871	---
Calcium	ppm	ASTM D5185m	1050	1364	---
Phosphorus	ppm	ASTM D5185m	995	849	---
Zinc	ppm	ASTM D5185m	1180	1063	---
Sulfur	ppm	ASTM D5185m	2600	3000	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	20	---
Sodium	ppm	ASTM D5185m		5	---
Potassium	ppm	ASTM D5185m	>20	215	---

INFRA-RED





	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.5	---
Nitration	Abs/cm	*ASTM D7624	>20	11.9	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.5	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	21.3	---
Base Number (BN)	mg KOH/g	ASTM D2896		5.4	---







OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.9	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0113986
Lab Number : 06229745
Unique Number : 11113238
Test Package : FLEET

Received : 08 Jul 2024
Tested : 09 Jul 2024
Diagnosed : 09 Jul 2024 - Wes Davis

BLUE MAX TRUCKING
 1015 E. WESTINGHOUSE BLVD.
 CHARLOTTE, NC
 US 28273
 Contact: Jody Greer
 jgreer@bluemaxtrucking.com
 T: (980)225-9968
 F: (704)588-2901

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)