




# OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id  
**728048-361999**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0107993</b>	GFL0108000	GFL0062965
Sample Date	Client Info	<b>25 Jun 2024</b>	16 Feb 2024	18 Jan 2023
Machine Age	hrs Client Info	<b>0</b>	0	11811
Oil Age	hrs Client Info	<b>0</b>	0	0
Oil Changed	Client Info	<b>Not Changed</b>	Changed	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>14</b>	8	10
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	0	<1
Nickel	ppm ASTM D5185m >4	<b>0</b>	0	<1
Titanium	ppm ASTM D5185m	<b>0</b>	0	<1
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>4</b>	2	2
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	0	1
Copper	ppm ASTM D5185m >330	<b>2</b>	<1	<1
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>6</b>	4	3
Barium	ppm ASTM D5185m 0	<b>0</b>	0	4
Molybdenum	ppm ASTM D5185m 60	<b>63</b>	58	59
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>911</b>	871	900
Calcium	ppm ASTM D5185m 1070	<b>1142</b>	1026	1039
Phosphorus	ppm ASTM D5185m 1150	<b>1098</b>	993	968
Zinc	ppm ASTM D5185m 1270	<b>1287</b>	1161	1221
Sulfur	ppm ASTM D5185m 2060	<b>3684</b>	3263	3310

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>4</b>	4	4
Sodium	ppm ASTM D5185m	<b>7</b>	4	7
Potassium	ppm ASTM D5185m >20	<b>2</b>	0	<1

## INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.3</b>	0.2	0.3
Nitration	Abs/cm *ASTM D7624 >20	<b>7.0</b>	5.5	7.2
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>18.3</b>	17.6	18.7


## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>14.1</b>	13.6	14.4
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.6</b>	9.3	8.7




# OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.3	13.7

## GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : GFL0107993  
 Lab Number : 06229803  
 Unique Number : 11113296  
 Test Package : FLEET

GFL Environmental - 823 - Central Missouri Hauling  
 24461 Oak Grove Lane  
 Sedalia, MO  
 US 65301  
 Contact: Terry Randolph  
 trandolph@gflenv.com  
 T: (660)631-2116  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)