




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**925049-370**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0121438</b>	GFL0121421	GFL0115852
Sample Date	Client Info	<b>02 Jul 2024</b>	17 May 2024	16 Apr 2024
Machine Age	hrs	<b>10815</b>	10749	10684
Oil Age	hrs	<b>66</b>	10749	10684
Oil Changed	Client Info	<b>Not Changed</b>	Changed	N/A
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>7</b>	29	26
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	2	2
Nickel	ppm ASTM D5185m >4	<b>0</b>	<1	0
Titanium	ppm ASTM D5185m	<b>0</b>	<1	0
Silver	ppm ASTM D5185m >3	<b>0</b>	<1	0
Aluminum	ppm ASTM D5185m >20	<b>2</b>	4	4
Lead	ppm ASTM D5185m >40	<b>0</b>	<1	<1
Copper	ppm ASTM D5185m >330	<b>1</b>	2	2
Tin	ppm ASTM D5185m >15	<b>0</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>11</b>	12	10
Barium	ppm ASTM D5185m 0	<b>0</b>	3	2
Molybdenum	ppm ASTM D5185m 60	<b>65</b>	64	61
Manganese	ppm ASTM D5185m 0	<b>0</b>	2	1
Magnesium	ppm ASTM D5185m 1010	<b>885</b>	924	902
Calcium	ppm ASTM D5185m 1070	<b>1108</b>	1158	1121
Phosphorus	ppm ASTM D5185m 1150	<b>1070</b>	1090	932
Zinc	ppm ASTM D5185m 1270	<b>1254</b>	1199	1077
Sulfur	ppm ASTM D5185m 2060	<b>3667</b>	3255	3260

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	7	5
Sodium	ppm ASTM D5185m	<b>3</b>	7	7
Potassium	ppm ASTM D5185m >20	<b>3</b>	2	0

## INFRA-RED




method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.2</b>	0.3	0.4
Nitration	Abs/cm *ASTM D7624 >20	<b>5.2</b>	8.2	7.3
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>17.2</b>	20.4	18.9

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>12.7</b>	16.8	14.8
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.9</b>	7.9	8.7







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.8</b>	13.7	13.4

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0121438      **Received** : 08 Jul 2024  
**Lab Number** : 06229856      **Tested** : 09 Jul 2024  
**Unique Number** : 11113349      **Diagnosed** : 09 Jul 2024 - Wes Davis  
**Test Package** : FLEET

GFL Environmental - 868 - Childersburg Fines Hauling (Alpine)  
 13737 Plant Rd  
 Childersburg, AL  
 US 35044  
 Contact: JONATHAN WILLIAMS  
 jonathan.williams@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)