

OIL ANALYSIS REPORT

Sample Rating Trend

VISCOSITY

Machine Id

731113-310101

Component Hydraulic System Fluid PETRO CANADA HYDREX MV 46 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

Viscosity of sample indicates oil is within ISO 32 range, advise investigate. Confirm oil type. The AN level is acceptable for this fluid.


SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0124134	GFL0087230	
Sample Date		Client Info		03 Jul 2024	07 Jul 2023	
Machine Age	hrs	Client Info		6345	4251	
Oil Age	hrs	Client Info		0	4251	
Oil Changed		Client Info		Not Changd	Not Changd	
Sample Status				ATTENTION	ABNORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	4	7	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>10	0	0	
Titanium	ppm	ASTM D5185m		0	<1	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>10	0	2	
Lead	ppm	ASTM D5185m	>10	0	<1	
Copper	ppm	ASTM D5185m	>75	2	2	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	<1	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	
Barium	ppm	ASTM D5185m	0	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m	1	0	<1	
Magnesium	ppm	ASTM D5185m	0	<1	2	
Calcium	ppm	ASTM D5185m	50	37	50	
Phosphorus	ppm	ASTM D5185m	330	253	291	
Zinc	ppm	ASTM D5185m	430	292	351	
Sulfur	ppm	ASTM D5185m	760	820	976	
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	3	8	
Sodium	ppm	ASTM D5185m		2	2	
Potassium	ppm	ASTM D5185m	>20	0	4	
FLUID CLEAN	LINESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	<mark>)</mark> 5625		
Particles >6µm		ASTM D7647	>1300	<mark> </mark> 1857		
Particles >14µm		ASTM D7647	>160	82		
Particles >21µm		ASTM D7647	>40	11		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	e 20/18/14		
FLUID DEGRAI	DATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.70	0.31	0.35	


Report Id: GFL836 [WUSCAR] 06230089 (Generated: 07/09/2024 19:38:54) Rev: 1


Contact/Location: GFL823,834,836,837,840 - Loyce Stewart - GFL836




OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
Vhite Metal	scalar	*Visual	NONE	NONE	NONE	
ellow Metal	scalar	*Visual	NONE	NONE	NONE	
recipitate	scalar	*Visual	NONE	NONE	NONE	
ilt	scalar	*Visual	NONE	NONE	NONE	
ebris	scalar	*Visual	NONE	NONE	🔺 MODER	
and/Dirt	scalar	*Visual	NONE	NONE	NONE	
ppearance	scalar	*Visual	NORML	NORML	- HAZY	
dor	scalar	*Visual	NORML	NORML	NORML	
mulsified Water	scalar	*Visual	>0.1	NEG	NEG	
ree Water	scalar	*Visual		NEG	NEG	
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
isc @ 40°C	cSt	ASTM D445	45.4	33.6	32.8	
SAMPLE IMAG	ES	method	limit/base	current	history1	history2
Color						no image
ottom						no image
GRAPHS						
Ferrous Alloys				Particle Cou	nt	
iron			491,520	1		T ²⁶
chromium			122,880			-24
nickel				Severe		
						+22
			30,720			
			7,680	Abnormal		
11/23			7,680	Abnormal		-20
52/LiuL			7,680	Abnormal		-20
	5		7,680	Abnormal	•••	-20
	5		7,680	Abnormal	•••	-20 -18 -16
Non-ferrous Metals	5		7,680 47(Clinn 47(Clinn 480 480 480 480 480 480 480 480 480 480	Abnormal		-20 -18 -16 -14
Non-ferrous Metals	5		7,680	Abnormal	•••	-20 -18 -16 -14
Non-ferrous Metals	5		7,680 47(Clinn 47(Clinn 480 480 480 480 480 480 480 480 480 480	Abnormal	•••	-2(-18 -16 -14 -14
Non-ferrous Metals	5		7,680 F2(Cl ^{III}) F2(Cl ^{III})	Abnomal	•••	-2(-18 -16 -14 -14
Non-ferrous Metals	5		7,680 F2(Cl ^{III}) F2(Cl ^{III})	Abnomal	•••	-20 -18 -16 -14 -12
Non-ferrous Metals	5		7,680 42(Cinn 480 480 480 120 30 480 480 480 480 480 480 480 48	Abnormal	144 214	-20 -18 -16 -14 -12 -10 -8 -8 -8 -8 -8 -8 -8 -71
Non-ferrous Metals	5		۲,680 +2/2017 +2/2017 +2/2017 480 480 120 30 480 480 480 480 480 480 480 48	Abnormal		-20 -18 -14 -14 -12 -10 -10 -8
Non-ferrous Metals	5		۲,680 +2/2017 +2/2017 +2/2017 480 480 120 30 480 480 480 480 480 480 480 48	Abnormal		-20 -18 -16 -14 -12 -10 -8 -8
Non-ferrous Metals	5		۲,680 +2/2017 +2/2017 +2/2017 480 480 120 30 480 480 480 480 480 480 480 48	Abnormal		-20 -18 -16 -14 -12 -10 -8 -8
Non-ferrous Metals	5		۲,680 +2/2017 +2/2017 +2/2017 480 480 120 30 480 480 480 480 480 480 480 48	Abnormal		-20 -18 -16 -14 -12 -10 -8 -8
Non-ferrous Metals	5		۲,680 +2/2017 +2/2017 +2/2017 480 480 120 30 480 480 480 480 480 480 480 48	Abnormal		-20 -18 -14 -14 -12 -10 -10 -8
Non-ferrous Metals	5		7,680 FJCEIN FJCEIN FJCEIN FJCEIN 1,920 480 120 300 60/HOX 0.60 120 0,00/HOX 0.00 100/HOX 0.00 100/HO	Abnormal		-24 -18 -14 -14 -14 -14 -14 -14 -14 -14 -14 -14
Non-ferrous Metals	5		7,680 1,920 FJCEIN	Abnormal		-20 -18 -14 -14 -12 -10 -10 -8



Report Id: GFL836 [WUSCAR] 06230089 (Generated: 07/09/2024 19:38:54) Rev: 1

Contact/Location: GFL823,834,836,837,840 - Loyce Stewart - GFL836