

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id **427168 - SW4747** Component **Transmission (Auto)** Fluid **DEXRON III (--- GAL)**

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The condition of the fluid is acceptable for the time in service.

	MATION	method	limit/base	current	history1	history2		
Sample Number		Client Info		GFL0066529	GFL0066528			
Sample Date		Client Info		01 Jul 2024	23 May 2023			
Machine Age	mls	Client Info		341025	319698			
Oil Age	mls	Client Info		21327	0			
Oil Changed		Client Info		N/A	Changed			
Sample Status				NORMAL	NORMAL			
CONTAMINATI	ON	method	limit/base	current	historv1	historv2		
Water		WC Method	>0.1	NEG	NEG			
WEAR METALS	S	method	limit/base	current	historv1	historv2		
Iron	nnm	ASTM D5185m	>160	90	131			
Chromium	nom	ASTM D5185m	>5	<1 c1	<1			
Nickel	ppm	ASTM D5185m	>5	<1	0			
Titanium	ppm	ASTM D5185m	20	<1	0			
Silver	ppm	ASTM D5185m	>5	<1	0			
Aluminum	ppm	ASTM D5185m	>50	19	22			
Lead	ppm	ASTM D5185m	>50	26	43			
Copper	ppm	ASTM D5185m	>225	55	73			
Tin	ppm	ASTM D5185m	>10	3	3			
Vanadium	nom	ASTM D5185m	210	۰ د1	0			
Cadmium	ppm	ASTM D5185m		<1	0			
ADDITIVES		method	limit/base	current	history1	history2		
Boron	maa	ASTM D5185m		154	181			
Barium	ppm	ASTM D5185m		0	0			
Molybdenum	ppm	ASTM D5185m		<1	<1			
Manganese	ppm	ASTM D5185m		1	1			
Magnesium	ppm	ASTM D5185m		2	4			
Calcium	ppm	ASTM D5185m		166	187			
Phosphorus	ppm	ASTM D5185m		376	455			
Zinc	ppm	ASTM D5185m		44	42			
Sulfur	ppm	ASTM D5185m		2055	2855			
CONTAMINAN	TS	method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>20	7	4			
Sodium	ppm	ASTM D5185m		4	4			
Potassium	ppm	ASTM D5185m	>20	3	3			
VISUAL		method	limit/base	current	history1	history2		
White Metal	scalar	*Visual	NONE	NONE	NONE			
Yellow Metal	scalar	*Visual	NONE	NONE	NONE			
Precipitate	scalar	*Visual	NONE	NONE	NONE			
Silt	scalar	*Visual	NONE	NONE	NONE			
Debris	scalar	*Visual	NONE	LIGHT	NONE			
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE			
Appearance	scalar	*Visual	NORML	NORML	NORML			
Odor	scalar	*Visual	NORML	NORML	NORML			
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG			
Free Water	scalar	*Visual		NEG	NEG			
3:50:39) Rev: 1					Submitted By	Submitted By: Erik Bazaldua		



OIL ANALYSIS REPORT



	FLUID PROP	ENTIES	methou	iiiiii/base	current	Thistory I	TIIStOryz
	Visc @ 40°C	cSt	ASTM D44	5 35.0	28.8	33.48	
	SAMPLE IMA	GES	method	limit/base	current	history1	history2
	Color				no image	no image	no image
	Bottom				no image	no image	no image
	GRAPHS						
	Ferrous Alloys						
120	- chromium						
	80						
	60						
	40						
	May23/23			Jul1/24			
	Non-ferrous Met	als					
	70 - copper lead						
	50 -						
	E. 40 -						
	20			Redna Skalen			
	10						
	a/23/23 +			Jul1/24 -			
	≥ Viscosity @ 40°(2					
	40 - Abnormal						
	35 - Base						
	40-04-30 20-04-30						
	25 -						
	20 - Abnormal			-			
	15			Jul1/24			
	≥ : WearCheck USA - 5	501 Madiso	on Ave., Ca	ry, NC 27513	GFL En	vironmental - 977 - M	ontgomery Hauling
r	: GFL0066529 : 06230668	Rece Teste	ived : ()8 Jul 2024 10 Jul 2024		17851	Highway 105 E Conroe. TX
	: 11114161 : FLEET	Diag	nosed :1	0 Jul 2024 - Jona	than Hester	Contact:	US 77306 CHRIS YOUNG



To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

christophery@gflenv.com

T:

F: