


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(51456Z) Walgreens - Tractor
 Machine Id
[Walgreens - Tractor] 136A63326
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	PCA0121291	PCA0103560	PCA0103488
Sample Date	Client Info	02 Jul 2024	21 Feb 2024	11 Dec 2023
Machine Age	mls Client Info	238595	206969	176273
Oil Age	mls Client Info	32000	60000	33111
Oil Changed	Client Info	Not Changed	Changed	Not Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >80	12	33	17
Chromium	ppm ASTM D5185m >5	<1	2	2
Nickel	ppm ASTM D5185m >2	0	0	0
Titanium	ppm ASTM D5185m	0	0	0
Silver	ppm ASTM D5185m >3	0	0	<1
Aluminum	ppm ASTM D5185m >30	4	17	11
Lead	ppm ASTM D5185m >30	0	0	0
Copper	ppm ASTM D5185m >150	17	32	31
Tin	ppm ASTM D5185m >5	0	0	<1
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 2	27	<1	1
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 50	47	53	58
Manganese	ppm ASTM D5185m 0	<1	<1	1
Magnesium	ppm ASTM D5185m 950	600	885	964
Calcium	ppm ASTM D5185m 1050	1808	1041	1083
Phosphorus	ppm ASTM D5185m 995	829	840	1018
Zinc	ppm ASTM D5185m 1180	982	1048	1285
Sulfur	ppm ASTM D5185m 2600	2870	2333	2614

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	5	6	5
Sodium	ppm ASTM D5185m	3	2	3
Potassium	ppm ASTM D5185m >20	7	31	19




INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.3	1	0.6
Nitration	Abs/cm *ASTM D7624 >20	7.6	10.8	8.5
Sulfation	Abs/.1mm *ASTM D7415 >30	22.8	23.9	21.7

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	20.9	22.4	18.7
Base Number (BN)	mg KOH/g ASTM D2896	8.8	4.8	6.7





OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	11.3	11.8	11.6

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0121291 **Received** : 08 Jul 2024
Lab Number : **06230990** **Tested** : 10 Jul 2024
Unique Number : 11114483 **Diagnosed** : 10 Jul 2024 - Sean Felton
Test Package : FLEET

Transervice - Shop 1369 - Berkeley-Waxahachie
 710 Ovilla Road
 Waxahachie, TX
 US 75167

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)