


# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Area  
**(N/A) Preferred Service-Yard Horse**  
 Machine Id  
**[Preferred Service-Yard Horse] 192A32002A**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (16 GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0126910</b>	PCA0120201	---
Sample Date	Client Info			<b>06 Jul 2024</b>	26 Mar 2024	---
Machine Age	hrs	Client Info		<b>1770</b>	689	---
Oil Age	hrs	Client Info		<b>689</b>	686	---
Oil Changed		Client Info		<b>Changed</b>	Changed	---
Sample Status				<b>NORMAL</b>	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	---
Water	WC Method	>0.2		<b>NEG</b>	NEG	---
Glycol	WC Method			<b>NEG</b>	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>76</b>	87	---
Chromium	ppm	ASTM D5185m	>20	<b>2</b>	3	---
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	1	---
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	---
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	---
Aluminum	ppm	ASTM D5185m	>20	<b>5</b>	9	---
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	---
Copper	ppm	ASTM D5185m	>330	<b>12</b>	94	---
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	2	---
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	---
Cadmium	ppm	ASTM D5185m		<b>0</b>	<1	---




ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>1</b>	17	---
Barium	ppm	ASTM D5185m	0	<b>0</b>	5	---
Molybdenum	ppm	ASTM D5185m	50	<b>58</b>	60	---
Manganese	ppm	ASTM D5185m	0	<b>1</b>	6	---
Magnesium	ppm	ASTM D5185m	950	<b>899</b>	843	---
Calcium	ppm	ASTM D5185m	1050	<b>1050</b>	1049	---
Phosphorus	ppm	ASTM D5185m	995	<b>930</b>	834	---
Zinc	ppm	ASTM D5185m	1180	<b>1177</b>	1116	---
Sulfur	ppm	ASTM D5185m	2600	<b>2500</b>	2607	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>9</b>	27	---
Sodium	ppm	ASTM D5185m		<b>2</b>	5	---
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	5	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>1.5</b>	1.3	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.7</b>	11.3	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>23.7</b>	22.0	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>20.4</b>	18.6	---
Base Number (BN)	mg KOH/g	ASTM D2896		<b>6.4</b>	7.2	---





# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.4	12.6

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0126910  
**Lab Number** : 06234519  
**Unique Number** : 11123353  
**Test Package** : FLEET

**Received** : 12 Jul 2024  
**Tested** : 12 Jul 2024  
**Diagnosed** : 12 Jul 2024 - Wes Davis

**Transervice - Shop 1920 - Preferred Service**  
 1955 W. North Avenue, Bldg K  
 Melrose Park, IL  
 US 60160

Contact: Tom Lindeman  
 tlindemann@transervice.com  
 T: (630)376-8946

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: