




# OIL ANALYSIS REPORT



Area  
**(P858111)**  
 Machine Id  
**713011**  
 Component  
**Diesel Engine**  
 Fluid  
**DIESEL ENGINE OIL SAE 40 (--- GAL)**

### Sample Rating Trend



**NORMAL**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0124437</b>	GFL0096974	GFL0096909
Sample Date	Client Info		<b>09 Jul 2024</b>	12 Apr 2024	29 Jan 2024
Machine Age	hrs	Client Info	<b>4034</b>	3448	2321
Oil Age	hrs	Client Info	<b>3448</b>	2321	0
Oil Changed	Client Info		<b>Changed</b>	Changed	Not Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>10</b>	11	<1
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	1	0
Nickel	ppm	ASTM D5185m >5	<b>0</b>	2	<1
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	2	2
Lead	ppm	ASTM D5185m >40	<b>0</b>	1	0
Copper	ppm	ASTM D5185m >330	<b>2</b>	2	0
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	2	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 250	<b>2</b>	8	10
Barium	ppm	ASTM D5185m 10	<b>0</b>	<1	<1
Molybdenum	ppm	ASTM D5185m 100	<b>67</b>	65	57
Manganese	ppm	ASTM D5185m	<b>0</b>	1	<1
Magnesium	ppm	ASTM D5185m 450	<b>929</b>	930	865
Calcium	ppm	ASTM D5185m 3000	<b>1163</b>	1141	972
Phosphorus	ppm	ASTM D5185m 1150	<b>1088</b>	1120	970
Zinc	ppm	ASTM D5185m 1350	<b>1264</b>	1263	1160
Sulfur	ppm	ASTM D5185m 4250	<b>2751</b>	3472	2878

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>3</b>	6	2
Sodium	ppm	ASTM D5185m >216	<b>&lt;1</b>	2	0
Potassium	ppm	ASTM D5185m >20	<b>4</b>	4	<1

## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.4</b>	0.3	0.1
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.1</b>	8.7	4.8
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.4</b>	19.8	17.4


## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>16.6</b>	16.0	12.7
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	<b>7.1</b>	7.1	8.8




# OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	<b>13.5</b>	13.3	13.7

## GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0124437  
**Lab Number** : 06234689  
**Unique Number** : 11123523  
**Test Package** : FLEET

**GFL Environmental - 031 - Greenville/Spartanburg**  
 1635 Antioch Church Rd  
 Piedmont, SC  
 US 29673

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact: TECHNICIAN ACCOUNT  
 catherine.anastasio@wearcheck.com

T:  
 F: