


OIL ANALYSIS REPORT

Sample Rating Trend





RC-1 (S/N 32457)

Reciprocating Compressor

CHEVRON REFRIGERATION OIL WF 68 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The water content is negligible. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The oil viscosity is higher than normal. The AN level is acceptable for this fluid.

| · GAL) | | Mar2020 | Sep2020 Mar2021 | Jan2023 Jul2023 Fe | b2024 | |
|------------------|----------|--------------|-----------------|--------------------|-------------|-------------|
| SAMPLE INFORI | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | PCA0125473 | PCA0115273 | PCA0106625 |
| Sample Date | | Client Info | | 01 Jul 2024 | 23 Feb 2024 | 09 Oct 2023 |
| Machine Age | hrs | Client Info | | 59007 | 56943 | 55568 |
| Oil Age | hrs | Client Info | | 7245 | 4523 | 2962 |
| Oil Changed | | Client Info | | Not Changd | Not Changd | Not Changd |
| Sample Status | | | | ATTENTION | ATTENTION | ATTENTION |
| WEAR METAL | S | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | <1 | 0 | 0 |
| Chromium | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| Nickel | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Silver | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >25 | 0 | 0 | 0 |
| Lead | ppm | ASTM D5185m | >25 | 0 | 0 | 0 |
| Copper | ppm | ASTM D5185m | >50 | 0 | 0 | 0 |
| Tin | ppm | ASTM D5185m | >15 | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Barium | ppm | ASTM D5185m | | 0 | 0 | 1 |
| Molybdenum | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Manganese | ppm | ASTM D5185m | | 0 | <1 | 0 |
| Magnesium | ppm | ASTM D5185m | | 0 | 0 | 2 |
| Calcium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Phosphorus | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Zinc | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Sulfur | ppm | ASTM D5185m | | 271 | 182 | 170 |
| CONTAMINAN | TS | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | <1 | <1 | 1 |
| Sodium | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Potassium | ppm | ASTM D5185m | >20 | <1 | 0 | 0 |
| Water | % | ASTM D6304 | >0.1 | 0.001 | 0.003 | 0.001 |
| ppm Water | ppm | ASTM D6304 | >1000 | 10 | 32 | 10.4 |
| FLUID CLEANI | LINESS | method | limit/base | current | history1 | history2 |
| Particles >4μm | | ASTM D7647 | >2500 | 268 | 616 | 1355 |
| Particles >6µm | | ASTM D7647 | >320 | 69 | 120 | 319 |
| Particles >14μm | | ASTM D7647 | >40 | 5 | 7 | 28 |
| Particles >21μm | | ASTM D7647 | | 1 | 2 | 9 |
| Particles >38μm | | ASTM D7647 | >3 | 0 | 0 | 0 |
| Particles >71μm | | ASTM D7647 | >3 | 0 | 0 | 0 |
| Oil Cleanliness | | ISO 4406 (c) | >18/15/12 | 15/13/10 | 16/14/10 | 18/15/12 |
| FLUID DEGRA | DATION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.014 | 0.013 | 0.014 |



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No. Lab Number

: PCA0125473 : 06235027 Unique Number : 11123861

Received **Tested**

: 12 Jul 2024 : 15 Jul 2024 Diagnosed Test Package : IND 2 (Additional Tests: KF, PrtCount)

: 15 Jul 2024 - Don Baldridge

261 Delaware St. Walton, NY US 13856 Contact: Cindy Scofield cindy.scofield@kraft.com

Contact/Location: Cindy Scofield - KRAWAL

To discuss this sample report, contact Customer Service at 1-800-237-1369. st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (607)865-8863

T: (607)865-2330