




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
926031-152524

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0106060	GFL0106199	GFL0106117
Sample Date	Client Info		09 Jul 2024	20 Mar 2024	14 Mar 2024
Machine Age	hrs	Client Info	12482	12052	0
Oil Age	hrs	Client Info	0	0	600
Oil Changed	Client Info		Not Changed	Not Changed	Changed
Sample Status			NORMAL	NORMAL	ATTENTION

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	0.9
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >110	11	7	77
Chromium	ppm	ASTM D5185m >4	0	<1	2
Nickel	ppm	ASTM D5185m >2	0	2	<1
Titanium	ppm	ASTM D5185m	0	<1	<1
Silver	ppm	ASTM D5185m >2	<1	<1	0
Aluminum	ppm	ASTM D5185m >25	2	3	4
Lead	ppm	ASTM D5185m >45	<1	1	<1
Copper	ppm	ASTM D5185m >85	2	33	80
Tin	ppm	ASTM D5185m >4	<1	1	<1
Vanadium	ppm	ASTM D5185m	0	<1	<1
Cadmium	ppm	ASTM D5185m	0	<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	9	16	17
Barium	ppm	ASTM D5185m 0	0	1	4
Molybdenum	ppm	ASTM D5185m 60	63	69	59
Manganese	ppm	ASTM D5185m 0	<1	<1	4
Magnesium	ppm	ASTM D5185m 1010	877	893	716
Calcium	ppm	ASTM D5185m 1070	1160	1272	1540
Phosphorus	ppm	ASTM D5185m 1150	1055	1124	1167
Zinc	ppm	ASTM D5185m 1270	1258	1292	1392
Sulfur	ppm	ASTM D5185m 2060	3553	3624	3228

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	11	4	18
Sodium	ppm	ASTM D5185m	4	0	27
Potassium	ppm	ASTM D5185m >20	3	3	3

INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.2	0.2	1
Nitration	Abs/cm	*ASTM D7624 >20	7.4	6.4	10.2
Sulfation	Abs/.1mm	*ASTM D7415 >30	19.4	18.3	23.2


FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	15.1	14.2	20.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	8.1	8.4	9.4




OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.9	13.8

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : GFL0106060
 Lab Number : 06235368
 Unique Number : 11124202
 Test Package : FLEET

Received : 15 Jul 2024
 Tested : 15 Jul 2024
 Diagnosed : 15 Jul 2024 - Wes Davis

GFL Environmental - 152 - Jacksonville
 7580 PHILIPS HWY
 Jacksonville, FL
 US 32256

Contact: GRANVILLE CARROLL
 gcarroll@gflenv.com
 T: 1(904)252-6815

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)