


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(51457Z) Walgreens - Tractor
 Machine Id
[Walgreens - Tractor] 136A63350
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	PCA0120789	PCA0120843	PCA0103499
Sample Date	Client Info	03 Jul 2024	06 May 2024	02 Jan 2024
Machine Age	mls Client Info	266419	233963	167637
Oil Age	mls Client Info	30000	60000	60000
Oil Changed	Client Info	Changed	Changed	Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >80	18	32	34
Chromium	ppm ASTM D5185m >5	1	3	3
Nickel	ppm ASTM D5185m >2	0	0	<1
Titanium	ppm ASTM D5185m	0	0	0
Silver	ppm ASTM D5185m >3	<1	<1	0
Aluminum	ppm ASTM D5185m >30	7	10	18
Lead	ppm ASTM D5185m >30	0	0	<1
Copper	ppm ASTM D5185m >150	21	42	55
Tin	ppm ASTM D5185m >5	0	<1	<1
Vanadium	ppm ASTM D5185m	0	0	<1
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 2	2	1	<1
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 50	62	66	62
Manganese	ppm ASTM D5185m 0	<1	1	1
Magnesium	ppm ASTM D5185m 950	931	1000	1065
Calcium	ppm ASTM D5185m 1050	1110	1141	1203
Phosphorus	ppm ASTM D5185m 995	1023	1011	1003
Zinc	ppm ASTM D5185m 1180	1194	1300	1357
Sulfur	ppm ASTM D5185m 2600	2821	2356	2204

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	6	7	7
Sodium	ppm ASTM D5185m	2	3	2
Potassium	ppm ASTM D5185m >20	12	20	39




INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.5	0.8	0.7
Nitration	Abs/cm *ASTM D7624 >20	9.1	12.2	11.3
Sulfation	Abs/.1mm *ASTM D7415 >30	20.7	23.5	23.3

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	17.5	24.6	22.9
Base Number (BN)	mg KOH/g ASTM D2896	7.1	5.7	5.4





OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.6	11.7

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0120789
Lab Number : 06235394
Unique Number : 11124228
Test Package : FLEET
Received : 15 Jul 2024
Tested : 15 Jul 2024
Diagnosed : 15 Jul 2024 - Wes Davis

Transervice - Shop 1369 - Berkeley-Waxahachie
 710 Ovilla Road
 Waxahachie, TX
 US 75167
 Contact: Robert Beal
 rbeal@transervice.com
 T: (972)923-9928
 F: (972)923-9919

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)