


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(N/A) Preferred Service-Yard Horse
 Machine Id
[Preferred Service-Yard Horse] 192A32003A
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (16 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0126902	PCA0120228	---
Sample Date	Client Info		09 Jul 2024	31 Mar 2024	---
Machine Age	hrs	Client Info	1801	770	---
Oil Age	hrs	Client Info	1031	760	---
Oil Changed	Client Info		Changed	Changed	---
Sample Status			NORMAL	NORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	---
Water	WC Method	>0.2	NEG	NEG	---
Glycol	WC Method		NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	96	97	---
Chromium	ppm	ASTM D5185m >20	4	4	---
Nickel	ppm	ASTM D5185m >4	0	1	---
Titanium	ppm	ASTM D5185m	0	<1	---
Silver	ppm	ASTM D5185m >3	0	0	---
Aluminum	ppm	ASTM D5185m >20	4	7	---
Lead	ppm	ASTM D5185m >40	0	1	---
Copper	ppm	ASTM D5185m >330	6	53	---
Tin	ppm	ASTM D5185m >15	0	2	---
Vanadium	ppm	ASTM D5185m	0	<1	---
Cadmium	ppm	ASTM D5185m	0	<1	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	0	6	---
Barium	ppm	ASTM D5185m 0	<1	6	---
Molybdenum	ppm	ASTM D5185m 50	54	56	---
Manganese	ppm	ASTM D5185m 0	2	7	---
Magnesium	ppm	ASTM D5185m 950	883	872	---
Calcium	ppm	ASTM D5185m 1050	987	1042	---
Phosphorus	ppm	ASTM D5185m 995	911	868	---
Zinc	ppm	ASTM D5185m 1180	1088	1122	---
Sulfur	ppm	ASTM D5185m 2600	2944	2748	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	11	25	---
Sodium	ppm	ASTM D5185m	4	6	---
Potassium	ppm	ASTM D5185m >20	0	4	---




INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	2	1.6	---
Nitration	Abs/cm	*ASTM D7624 >20	12.1	11.3	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	24.5	22.5	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	20.0	19.4	---
Base Number (BN)	mg KOH/g	ASTM D2896	7.1	7.5	---





OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.1	12.6

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0126902
Lab Number : 06235470
Unique Number : 11124304
Test Package : FLEET

Received : 15 Jul 2024
Tested : 15 Jul 2024
Diagnosed : 15 Jul 2024 - Wes Davis

Transervice - Shop 1920 - Preferred Service
 1955 W. North Avenue, Bldg K
 Melrose Park, IL
 US 60160

Contact: Tom Lindeman
 tlindemann@transervice.com
 T: (630)376-8946

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: