




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
128015-1066

Component
Diesel Engine

Fluid
CHEVRON DELO 400 XLE 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0124160	GFL0099629	---
Sample Date	Client Info	09 Jul 2024	12 Feb 2024	---
Machine Age	hrs Client Info	4837	4718	---
Oil Age	hrs Client Info	0	600	---
Oil Changed	Client Info	Changed	Changed	---
Sample Status		NORMAL	NORMAL	---

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	---
Water	WC Method >0.2	NEG	NEG	---
Glycol	WC Method	NEG	NEG	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >110	11	32	---
Chromium	ppm ASTM D5185m >4	<1	2	---
Nickel	ppm ASTM D5185m >2	0	<1	---
Titanium	ppm ASTM D5185m	<1	<1	---
Silver	ppm ASTM D5185m >2	0	0	---
Aluminum	ppm ASTM D5185m >25	2	5	---
Lead	ppm ASTM D5185m >45	0	1	---
Copper	ppm ASTM D5185m >85	2	4	---
Tin	ppm ASTM D5185m >4	0	<1	---
Vanadium	ppm ASTM D5185m	0	<1	---
Cadmium	ppm ASTM D5185m	0	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	8	7	---
Barium	ppm ASTM D5185m	0	0	---
Molybdenum	ppm ASTM D5185m	59	61	---
Manganese	ppm ASTM D5185m	<1	<1	---
Magnesium	ppm ASTM D5185m	937	915	---
Calcium	ppm ASTM D5185m	1108	1256	---
Phosphorus	ppm ASTM D5185m 760	1010	1027	---
Zinc	ppm ASTM D5185m 830	1200	1248	---
Sulfur	ppm ASTM D5185m 2770	3490	3012	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	3	4	---
Sodium	ppm ASTM D5185m	2	<1	---
Potassium	ppm ASTM D5185m >20	1	4	---

INFRA-RED




method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.2	0.4	---
Nitration	Abs/cm *ASTM D7624 >20	6.8	10.8	---
Sulfation	Abs/.1mm *ASTM D7415 >30	18.0	21.0	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.1	18.0	---
Base Number (BN)	mg KOH/g ASTM D2896 10.7	9.3	6.3	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.9	13.8	13.6	---

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0124160 **Received** : 15 Jul 2024
Lab Number : 06235499 **Tested** : 15 Jul 2024
Unique Number : 11124333 **Diagnosed** : 16 Jul 2024 - Don Baldrige
Test Package : FLEET

GFL Environmental - 633 - Grand Haven
 1680 Peach St
 Whitehall, MI
 US 49461
 Contact: Derek Kater
 dkater@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)