




OIL ANALYSIS REPORT



Machine Id
834033
 Component
Natural Gas Engine
 Fluid
DIESEL ENGINE OIL (--- GAL)

Sample Rating Trend



NORMAL



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0127186	GFL0122083	GFL0116587
Sample Date	Client Info		10 Jul 2024	13 Jun 2024	21 May 2024
Machine Age	hrs	Client Info	1516	1340	1182
Oil Age	hrs	Client Info	176	158	1182
Oil Changed	Client Info		Not Chngd	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	8	11	49
Chromium	ppm	ASTM D5185m >4	<1	<1	4
Nickel	ppm	ASTM D5185m >2	0	0	2
Titanium	ppm	ASTM D5185m	<1	<1	<1
Silver	ppm	ASTM D5185m >3	<1	0	<1
Aluminum	ppm	ASTM D5185m >9	3	4	20
Lead	ppm	ASTM D5185m >30	0	0	2
Copper	ppm	ASTM D5185m >35	2	1	13
Tin	ppm	ASTM D5185m >4	<1	0	1
Vanadium	ppm	ASTM D5185m	<1	<1	<1
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	22	22	4
Barium	ppm	ASTM D5185m	<1	0	0
Molybdenum	ppm	ASTM D5185m	54	52	62
Manganese	ppm	ASTM D5185m	<1	2	11
Magnesium	ppm	ASTM D5185m	574	554	805
Calcium	ppm	ASTM D5185m	1570	1553	1614
Phosphorus	ppm	ASTM D5185m	738	743	790
Zinc	ppm	ASTM D5185m	981	995	1031
Sulfur	ppm	ASTM D5185m	2313	2711	2857

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >+100	5	5	19
Sodium	ppm	ASTM D5185m >75	2	4	6
Potassium	ppm	ASTM D5185m >20	5	9	69

INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	0	0	0
Nitration	Abs/cm	*ASTM D7624 >20	8.7	8.8	12.8
Sulfation	Abs/.1mm	*ASTM D7415 >30	19.7	19.5	26.2

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	16.6	16.8	22.7
Base Number (BN)	mg KOH/g	ASTM D2896	7.1	7.5	3.6







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.9	14.8	14.6

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0127186 **Received** : 15 Jul 2024
Lab Number : 06235553 **Tested** : 15 Jul 2024
Unique Number : 11124387 **Diagnosed** : 15 Jul 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 652 - Fredericksburg Hauling
 10954 Houser Drive
 Fredericksburg, VA
 US 22408
 Contact: WILLIAM MILO
 wmilo@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: