

## **OIL ANALYSIS REPORT**

Sample Rating Trend



### Machine Id I NG PCA06236224 NOT GIVEN PCA06236224 Gearbox

Fluid {not provided} (--- GAL)

#### DIAGNOSIS

#### Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

#### 📥 Wear

The aluminum level is abnormal. All other component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


#### Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA06236224		
Sample Date		Client Info		14 Jul 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
PQ		ASTM D8184		44		
Iron	ppm	ASTM D5185m	>200	51		
Chromium	ppm	ASTM D5185m	>15	<1		
Nickel	ppm	ASTM D5185m	>15	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	<u> </u>		
Lead	ppm	ASTM D5185m	>100	0		
Copper	ppm	ASTM D5185m	>200	3		
Tin	ppm	ASTM D5185m	>25	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		14		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		8		
Calcium	ppm	ASTM D5185m		2985		
Phosphorus	ppm	ASTM D5185m		583		
Zinc	ppm	ASTM D5185m		1249		
Sulfur	ppm	ASTM D5185m		1452		
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	27		
Sodium	ppm	ASTM D5185m		4		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.18		



# **OIL ANALYSIS REPORT**







VISUAL		method	limit/base	current	history1	histor
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt		*Visual	NONE	NONE		
	scalar					
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPER	RTIES	method	limit/base	current	history1	histo
Visc @ 40°C	cSt	ASTM D445		282		
SAMPLE IMAG	ES	method	limit/base	current	history1	histo
Color					no image	no ima
Bottom					no image	no ima
GRAPHS						1
Ferrous Alloys				PQ		
60 T			220			
40			200	- Severe		
E di normanickel			180	, <b>,</b> ,		
20			160			
<sup>24</sup> <sup>10</sup>			140 *			
Jui14,/24			120 Juli 4/24	•		
Non-ferrous Metals			- 2 100	Abnormal		
8 - copper			60			
Ctin						
			40	)		
2				•		
0			45 (			
Jul14/2 <sup>4</sup>			Jul14/24	Jul14/24		
J Viscosity @ 40°C			7	,		
<sup>300</sup> T			_ 0.20	Acid Number		
280 -			(B)HC			
© 260 € 240 <b>Abnormal</b>			월 0.15 문	1		
9 240			ے او 0.10	) +		
220 Abnormal			(B)H01 WH01 WH01 WH01 WH01 WH01 WH01 WH01 W			
180			0.00	,L.,		
Jul14/24			Jul14/24	Jul14/24		
Juli 1			llul	1uL		
<ul> <li>WearCheck USA - 501</li> <li>PCA06236224</li> <li>06236224</li> </ul>	Madiso Recei Teste	ived : 18	v, NC 27513 5 Jul 2024 6 Jul 2024	WEST HERSH	THE HERSH EY - TECHNICAL ASSURANCE,	

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Contact/Location: CLINTON ZOHNER - HERHER

Page 2 of 2

F: (717)374-4594

clintzohner@hersheys.com T: (717)374-4846