


# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL



Machine Id
427192
Component
Transmission (Auto)
Fluid
DEXRON III (--- GAL)

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the fluid.


## **Fluid Condition**

The condition of the fluid is acceptable for the time in service.

		Feb 2023	Jul2023 Jul2023	Jan2024 Jun2024	Jul2024	
SAMPLE INFOR	AOITANA	method	limit/base	current	history1	history2
	IVIATION		IIIIIIVDase			
Sample Number		Client Info		GFL0128742	GFL0123523	GFL0105496
Sample Date		Client Info		13 Jul 2024	20 Jun 2024	05 Jan 2024
Machine Age	mls	Client Info		355324	355324	341405
Oil Age	mls	Client Info		355324	355324	341405
Oil Changed		Client Info		Not Changd	Changed	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METAL	.S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	10	21	11
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>50	<1	4	5
Lead	ppm	ASTM D5185m	>50	<1	0	0
Copper	ppm	ASTM D5185m	>225	161	101	58
Tin	ppm	ASTM D5185m	>10	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
	nnm			58	14	13
Boron	ppm	ASTM D5185m			0	0
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		0	2	<1
Calcium	ppm	ASTM D5185m		598	283	276
Phosphorus	ppm	ASTM D5185m		545	400	434
Zinc	ppm	ASTM D5185m		0	27	28
Sulfur	ppm	ASTM D5185m		1654	901	795
CONTAMINAN	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	4	10	8
Sodium	ppm	ASTM D5185m		3	4	5
Potassium	ppm	ASTM D5185m	>20	<1	2	2
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
:42:55) Rev: 1		2			ed Bv: TECHNIC	





## **OIL ANALYSIS REPORT**






## **GRAPHS**









Certificate 12367

Laboratory Sample No.

Test Package : FLEET

Lab Number : 06240809

: GFL0128742 Unique Number : 11129643

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Tested Diagnosed

: 18 Jul 2024 : 19 Jul 2024

: 22 Jul 2024 - Don Baldridge

GFL Environmental - 983 - Sugar Land Hauling 16011 West Belfort Street

Sugar Land, TX

US 77498 Contact: TECHNICIAN ACCOUNT

wcgfldemo@gmail.com

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) T:

F: