

CONSTRUCTION EQUIPMENT

8*132922 VOLVO A40G 341497 - BOGIE/CENTER AXLE



Sample No: VCE035152

Oil Type: VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3

Job No: 8*132922

VOLVO	INFORMATIO	Π		
	INFURMATIU			
Sample Number		VCE035152	 	
Sample Date		28 Nov 2017	 	
Machine Hours		1646	 	
Oil Hours		1646	 	
Oil Changed		Not Changd	 	
Sample Status		ABNORMAL	 	
OIL CON	NITION			
Visc @ 40°C	cSt	<u>▲</u> 51.0	 	
VOLVO				
CONTAN	INATION			
Silicon	ppm	3	 	
Sodium	ppm	3	 	
Potassium	ppm	1	 	
rotassium	ррпп	•	 	
VOLVO				
WEAR M	TETALS			
Iron	ppm	■267	 	
Copper	ppm	■ 3	 	
Lead	ppm	■0	 	
Tin	ppm	■ 0	 	
Aluminum	ppm	-<1	 	
Chromium	ppm	4	 	
Molybdenum	ppm	■8	 	
Nickel	ppm	1	 	
Titanium	ppm	<1	 	
Silver	ppm	0	 	
Manganese	ppm	11	 	
Vanadium	ppm	0	 	
VOLVO	IFC		 	
ADDITIV	EZ.			
Calcium	ppm	<u> </u>	 	
Magnesium	ppm	<u> </u>	 	
Zinc	ppm	<u> </u>	 	
Phosphorus	ppm	<u> </u>	 	
Barium	ppm	0	 	
Boron	ppm	<u> </u>	 	



STRONGCO EQUIPMENT

655 MOUNTDALE AVENUE THUNDER BAY, ON CA P7E 6E5 Contact: Jean-Luc Antier jantier@strongco.com T: (807)475-3052 F: (807)473-0921

Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. Viscosity of sample indicates oil is within SAE 75W80 range, advise investigate. This plus the additive levels indicates that this is not the same brand, or type of oil as reported. The condition of the oil is acceptable for the time in service.

Depot:CHATHUUnique No:4604806Signed:Kevin MarsonReport Date:05 Dec 2017



CONSTRUCTION EQUIPMENT





