

CONSTRUCTION EQUIPMENT

JOHNSON&HERBERT VOLVO A30G 742128 - DIESEL ENGINE

Sample No: PP530750

Silicon

Sodium

Potassium

Oil Type: PETRO CANADA DURON UHP 0W40

Job No: JOHNSON&HERBERT

ppm

ppm

ppm

4

1

0

SAMPLE	INFORMAT	ION		
Sample Number	-	PP530750	 	
Sample Date		06 Jun 2019	 	
Machine Hours		1002	 	
Oil Hours		250	 	
Oil Changed		Changed	 	
Sample Status		ABNORMAL	 	
OIL COND	ITION			
Visc @ 100°C	cSt	1 0.7	 	
Oxidation (PA)	%	60	 	
CONTAMI	NATION			
Soot %	%	0.1	 	
Nitration (PA)	%	59	 	
Sulfation (PA)	%	53	 	
Glycol	%	NEG	 	
Fuel	%	2.8	 	

VOLVO	METALC			
WEAK	METALS			
Iron	ppm	□ 7	 	
Copper	ppm	2	 	
Lead	ppm	■<1	 	
Tin	ppm	■ 0	 	
Aluminum	ppm	1	 	
Chromium	ppm	■<1	 	
Molybdenum	ppm	■ 53	 	
Nickel	ppm	■ 0	 	
Titanium	ppm	0	 	
Silver	ppm	■ 0	 	
Manganese	ppm	■<1	 	
Vanadium	ppm	0	 	

ADDITIVES							
Calcium	ppm	1058					
Magnesium	ppm	■843					
Zinc	ppm	1100					
Phosphorus	ppm	941					
Barium	ppm	0					
Boron	ppm	■8					



STRONGCO EQUIPMENT-EDMONTON

25616 117 Ave NW Acheson, AB CA T7X 6C2 Contact: Jonathan Morton jmorton@strongco.com T: (780)464-1909 F: (780)464-0434

Diagnosis

Resample at the next service interval to monitor. No other corrective action is recommended at this time.All component wear rates are normal. Light fuel dilution occurring. No other contaminants were detected in the oil. Viscosity of sample indicates oil is within SAE 30 range, advise investigate. The condition of the oil is acceptable for the time in service.

Depot:VOLVO3908Unique No:4888998Signed:Kevin MarsonReport Date:27 Jun 2019



CONSTRUCTION EQUIPMENT





