

## **CONSTRUCTION EQUIPMENT**

JOHNSONGHERBERT VOLVO A30G 742128 - REAR RIGHT FINAL DR

Sample No: PP396732

Oil Type: GEAR OIL SAE 80W90

Job No: JOHNSON&HERBERT

VOLVO				
	E INFORMATIO	N		
Sample Number		PP396732	 	
Sample Date		06 Jun 2019	 	
Machine Hours		1002	 	
Oil Hours		1002	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
OIL CON	NITIAN			
Visc @ 40°C	cSt	<b>136</b>	 	
VOLVO				
CONTAN	MINATION			
Silicon	ppm	<b>1</b>	 	
Sodium	ppm	<b>1</b>	 	
Potassium	ppm	<b>2</b>	 	
	ρρ			
VOLVO	ACTAL C			
WEAR N	NE I ALS			
Iron	ppm	<b>60</b>	 	
Copper	ppm	<b>■</b> 2	 	
Lead	ppm	<b>■</b> <1	 	
Tin	ppm	<b>■</b> 0	 	
Aluminum	ppm	■0	 	
Chromium	ppm	■1	 	
Molybdenum	ppm	<b>■</b> <1	 	
Nickel	ppm	<b>■&lt;1</b>	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	2	 	
Vanadium	ppm	0	 	
VOLVO				
ADDITIV	/ES			
Calcium	ppm	<b>1</b> 5	 	
Magnesium	ppm	<b></b>	 	
Zinc	ppm	■18	 	
Phosphorus	ppm	1044	 	
Barium	ppm	■0	 	
Boron	ppm	<b>■</b> 173	 	
	111111111111111111111111111111111111111	_		



#### STRONGCO EQUIPMENT-EDMONTON

25616 117 Ave NW Acheson, AB CA T7X 6C2 Contact: Jonathan Morton jmorton@strongco.com T: (780)464-1909 F: (780)464-0434

### Diagnosis

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.

All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO3908Unique No:4889119Signed:Wes DavisReport Date:27 Jun 2019



# **CONSTRUCTION EQUIPMENT**





