

## CONSTRUCTION EQUIPMENT VOLVO EC300E 312441 - HYDRAULIC SYSTEM



Sample No: VCP274395

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No:

VOLVO	INFORMATION				
	INFORMATION				_
Sample Number		VCP274395			
Sample Date		20 Sep 2020			
Machine Hours		2000			
Oil Hours		2000			
Oil Changed		Not Changd			
Sample Status		NORMAL			
VOLVO					
OIL CONDITION					
Visc @ 40°C	cSt	■39.0			
		_			
VOLVO	INATION				
CONTAM	INATIUN	<u>.</u>			
Particles >4µm		<b>1463</b>			
Particles >6µm		■333			
Particles >14µm		■24			
ISO 4406:1999 (c)		18/16/12			
Silicon	ppm	■3			
Sodium	ppm	■0			
Potassium	ppm	<b>■</b> <1			
VOLVO					
WEAR M	ETALS				
Iron	ppm	■3			
Copper	ppm	■32			
Lead	ppm	<b>1</b>			
Tin	ppm	0			
Aluminum	ppm	<b>■</b> <1			
Chromium	ppm	<b>■</b> <1			
Molybdenum	ppm	<b>■</b> 0			
Nickel	ppm	<b>■ &lt;1</b>			
Titanium	ppm	<1			
Silver	ppm	0			
Manganese	ppm	■ 0			
Vanadium	ppm	0			
ADDITIVES					
Calcium	ppm	<b>67</b>			
Magnesium	ppm	<b>=</b> <1			
Zinc	ppm	<b>485</b>			
Phosphorus	ppm	■393			
Barium	ppm	<b>■</b> <1			
Boron	ppm	<1			



Strongco Equipment 5179 Fountain St N. Breslau, ON CA NOB 1M0 Contact: Matt Crisci mcrisci@strongco.com T: (519)744-3518 F: (519)744-3284

## Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The condition of the oil is acceptable for the time in service.

Depot:CASKITUnique No:5111472Signed:Wes DavisReport Date:08 Oct 2020

Contact/Location: Matt Crisci - CASKIT



## **CONSTRUCTION EQUIPMENT**





## GRAPHS

