



CONSTRUCTION EQUIPMENT

317152 VOLVO A25G 752165 - BOGIE/CENTER AXLE



Sample No: VCP331934
Oil Type: VOLVO API GL-5 SAE 75W90
Job No: 317152



SAMPLE INFORMATION

Sample Number	VCP331934	---	---	---
Sample Date	07 Mar 2022	---	---	---
Machine Hours	1372	---	---	---
Oil Hours	1372	---	---	---
Oil Changed	Changed	---	---	---
Sample Status	ABNORMAL	---	---	---

STRONGCO EQUIPMENT INC (STE- FOY)

175, rue de Rotterdam
 St-Augustin-de-Desmaures, QC
 CA G3A 2K2
 Contact: Michel Lepage
 mlepage@strongco.com
 T: (418)870-1700
 F: (418)870-1701



OIL CONDITION

Visc @ 40°C	cSt	▲ 57.0	---	---	---
-------------	-----	--------	-----	-----	-----



CONTAMINATION

Silicon	ppm	■ 6	---	---	---
Sodium	ppm	■ 2	---	---	---
Potassium	ppm	■ 5	---	---	---



WEAR METALS

Iron	ppm	■ 279	---	---	---
Copper	ppm	■ 47	---	---	---
Lead	ppm	■ 1	---	---	---
Tin	ppm	■ 2	---	---	---
Aluminum	ppm	■ <1	---	---	---
Chromium	ppm	■ 6	---	---	---
Molybdenum	ppm	■ 7	---	---	---
Nickel	ppm	■ 4	---	---	---
Titanium	ppm	0	---	---	---
Silver	ppm	0	---	---	---
Manganese	ppm	■ 18	---	---	---
Vanadium	ppm	0	---	---	---



ADDITIVES

Calcium	ppm	582	---	---	---
Magnesium	ppm	■ 2	---	---	---
Zinc	ppm	242	---	---	---
Phosphorus	ppm	1454	---	---	---
Barium	ppm	■ 4	---	---	---
Boron	ppm	175	---	---	---

Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill. Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition. Les taux d'usure de tous les composants sont normaux. Il n'y a aucun indice de contamination dans l'huile. La viscosité de l'échantillon se situe dans la portée de l'SAE 80; nous vous conseillons de vérifier. Ceci, en plus des niveaux d'additifs, indique que la marque ou le type d'huile ne correspond pas à ce qui a été signalé. L'état de l'huile est acceptable pour la durée de service.

Depot: VOLVO0228
Unique No: 5369972
Signed: Kevin Marson
Report Date: 14 Mar 2022



CONSTRUCTION EQUIPMENT



GRAPHS

