



CONSTRUCTION EQUIPMENT

TRIPLE M 373002 VOLVO EC480E 315055 - FRONT RIGHT FINAL DRIVE



Sample No: VCP381985
Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5
Job No: 373002



SAMPLE INFORMATION

| | | | | |
|---------------|-------------|-----|-----|-----|
| Sample Number | VCP381985 | --- | --- | --- |
| Sample Date | 21 Jul 2023 | --- | --- | --- |
| Machine Hours | 664 | --- | --- | --- |
| Oil Hours | 500 | --- | --- | --- |
| Oil Changed | Changed | --- | --- | --- |
| Sample Status | NORMAL | --- | --- | --- |

STRONGCO EQUIPMENT (CE)

1051 Heritage Rd.
Burlington, ON
CA L7L 4Y1
Contact: Sue Hooton
shooton@strongco.com
T: (905)331-3835
F: (905)643-6077



OIL CONDITION

| | | | | | |
|-------------|-----|-------|-----|-----|-----|
| Visc @ 40°C | cSt | █ 176 | --- | --- | --- |
|-------------|-----|-------|-----|-----|-----|



CONTAMINATION

| | | | | | |
|-----------|-----|-----|-----|-----|-----|
| Silicon | ppm | █ 7 | --- | --- | --- |
| Sodium | ppm | █ 2 | --- | --- | --- |
| Potassium | ppm | █ 2 | --- | --- | --- |



WEAR METALS

| | | | | | |
|------------|-----|-------|-----|-----|-----|
| Iron | ppm | █ 294 | --- | --- | --- |
| Copper | ppm | █ <1 | --- | --- | --- |
| Lead | ppm | █ 0 | --- | --- | --- |
| Tin | ppm | █ 0 | --- | --- | --- |
| Aluminum | ppm | █ <1 | --- | --- | --- |
| Chromium | ppm | █ 3 | --- | --- | --- |
| Molybdenum | ppm | █ <1 | --- | --- | --- |
| Nickel | ppm | █ 0 | --- | --- | --- |
| Titanium | ppm | █ <1 | --- | --- | --- |
| Silver | ppm | █ 0 | --- | --- | --- |
| Manganese | ppm | █ 4 | --- | --- | --- |
| Vanadium | ppm | █ 0 | --- | --- | --- |



ADDITIVES

| | | | | | |
|------------|-----|-------|-----|-----|-----|
| Calcium | ppm | █ 8 | --- | --- | --- |
| Magnesium | ppm | █ 2 | --- | --- | --- |
| Zinc | ppm | █ 11 | --- | --- | --- |
| Phosphorus | ppm | █ 289 | --- | --- | --- |
| Barium | ppm | █ 3 | --- | --- | --- |
| Boron | ppm | █ <1 | --- | --- | --- |

Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. Additive levels indicate the addition of a different brand, or type of oil. The condition of the oil is acceptable for the time in service.

Depot: VOLVO0252
Unique No: 5619356
Signed: Kevin Marson
Report Date: 08 Aug 2023



CONSTRUCTION EQUIPMENT



GRAPHS

