

CONSTRUCTION EQUIPMENT 375374 VOLVO A25F 80028 - MIDDLE AXLE



Sample No: VCP392468

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: 375374

SAMPLE	INFORMATIO	N			
Sample Number		VCP392468			
Sample Date		15 Aug 2023			
Machine Hours		16156			
Oil Hours		0			
Oil Changed		Changed			
Sample Status		ABNORMAL			
VOLVO					
OIL CONDITION					
Visc @ 40°C	cSt	109			
VOLVO	IINATION				
CONTAM	INATION				
Silicon	ppm	11			
Sodium	ppm	1			
Potassium	ppm	■ <1			
WEAR METALS					
Iron	ppm	■38			
Copper	ppm	2			
Lead	ppm	□ <1			
Tin	ppm	■ 0			
Aluminum	ppm	2			
Chromium	ppm	■ <1			
Molybdenum	ppm	1			
Nickel	ppm	■<1			
Titanium	ppm	<1			
Silver	ppm	<1			
Manganese	ppm	■<1			
Vanadium	ppm	0			
ADDITIV	ES				
Calcium	ppm	2433			
Magnesium	ppm	■8			
Zinc	ppm	987			
Phosphorus	ppm	■883			
Barium	ppm	O			
Boron	ppm	2			



STRONGCO EQUIPMENT

54 IBER ROAD OTTAWA, ON CA K2S 1E8 Contact: Daniel Simard dsimard@strongco.com T: (613)836-6633 F: (613)836-2614

Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor. The fluid was specified as VOLVO PREMIUM GEAR OIL 80W-90 GL-5, however, a fluid match indicates that this fluid is SAE 40 Transmission/Drive Train Oil. Please confirm the oil type and grade on your next sample.All component wear rates are normal. There is no indication of any contamination in the oil. Viscosity of sample indicates oil is within SAE 40 range, advise investigate. This plus the additive levels indicates that this is not the same brand, or type of oil as reported. The condition of the oil is acceptable for the time in service.

Depot:SHESTIUnique No:5629564Signed:Kevin MarsonReport Date:18 Aug 2023



CONSTRUCTION EQUIPMENT





GRAPHS

