

# CONSTRUCTION EQUIPMENT 374467 VOLVO A40G 353347 - FRONT AXLE



Sample No: VCP394848

Oil Type: VOLVO SUPER GEAR OIL 75W-80-GO102

**Job No:** 374467

ZAMPI F	INFORMATIO	N		
	. IINI UNIMA I IU	VCP394848	 	
Sample Number				
Sample Date		11 Aug 2023	 	
Machine Hours		1014		
Oil Channel		1000	 	
Oil Changed		Not Changd	 	
Sample Status		NORMAL	 	
VOLVO				
OIL CON	DITION			
Visc @ 40°C	cSt	<b>51.2</b>	 	
		_		
VOLVO	MATION			
	MINATION			
Silicon	ppm	■4	 	
Sodium	ppm	■3	 	
Potassium	ppm	<b>5</b>	 	
WEAR M	AFTAI S			
Iron	-	338	 	
Copper	ppm	<b>■</b> 336	 	
Lead	ppm	<b>0</b>	 	
Tin	ppm	<b>0</b>	 	
Aluminum	ppm	<b>□</b> <1	 	
Chromium	ppm	<b>■</b> 5	 	
Molybdenum	ppm	_	 	
Nickel	ppm	<b>■</b> 6	 	
Titanium	ppm	0	 	
	ppm	0		
Silver	ppm	<b>□</b> 10	 	
Manganese	ppm		 	
Vanadium	ppm	0	 	
VOLVO				
ADDITIV	ES			
Calcium	ppm	14	 	
Magnesium	ppm	<b>-&lt;1</b>	 	
Zinc	ppm	10	 	
Phosphorus	ppm	2445	 	
Barium	ppm	<b>■</b> <1	 	
Boron	ppm	<b>229</b>	 	
		_		



#### **Strongco Equipment**

5179 Fountain St N.
Breslau, ON
CA NOB 1M0
Contact: Nick Sanders
nsanders@strongco.com
T: (519)744-3518
F: (519)744-3284

### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:CASKITUnique No:5629944Signed:Kevin MarsonReport Date:21 Aug 2023



## **CONSTRUCTION EQUIPMENT**





#### GRAPH

