Sample No: VCP393046

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: 396718

SAMPLE	INFORMATIO	N			
Sample Number		VCP393046			
Sample Date		07 Mar 2024			
Machine Hours		4722			
Oil Hours		4000			
Oil Changed		Changed			
Sample Status		ABNORMAL			
OIL CONDITION					
Visc @ 40°C	cSt	△ 45.5			
VISC @ 40 C	CSt	45.5			
VOLVO					
CONTAN	MINATION				
Water	%	NEG			
Silicon	ppm	■27			
Sodium	ppm	■8			
Potassium	ppm	■ 4			
VOLVO					
WEAR N	METALS				
Iron	ppm	□88			
Copper	ppm	<u> </u>			
Lead	ppm				
Tin	ppm	■0			
Aluminum	ppm	1			
Chromium	ppm	-< 1			
Molybdenum	ppm	■8			
Nickel	ppm	■<1			
Titanium	ppm	0			
Silver	ppm	0			
Manganese	ppm	1			
Vanadium	ppm	0			
VOLVO					
ADDITIV	/ES				
Calcium	ppm	1235			
Magnesium	ppm	9			
Zinc	ppm	504			
Phosphorus	ppm	2072			
Barium	ppm				
Boron	ppm	163			



STRONGCO EQUIPMENT (CE)

1051 Heritage Rd.
Burlington, ON
CA L7L 4Y1
Contact: Michael Hribar
mhribar@strongco.com
T:
F: (905)643-6077

Diagnosis

Confirm the source of the lubricant being utilized for top-up/fill. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. Viscosity of sample indicates oil is within SAE 75W80 range, advise investigate. This plus the additive levels indicates that this is not the same brand, or type of oil as reported. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0252Unique No:5746707Signed:Kevin MarsonReport Date:13 Mar 2024



CONSTRUCTION EQUIPMENT





