Sample No: VCP303033

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: W125703

SAMPLE	INFORMATIO	N		
Sample Number	_	VCP303033	VCP275569	
Sample Date		13 May 2021	26 Mar 2020	
Machine Hours		2298	522	
Oil Hours		1000	0	
Oil Changed		Changed	Not Changd	
Sample Status		ABNORMAL	ABNORMAL	
		712710711111112	7.07.07.07.0	
VOLVO	DITION			
OIL CON	UIIIUN			
Visc @ 40°C	cSt	232	182	
CUNTAN	INATION			
Water	%	NEG	NEG	
Silicon	ppm	<u>^</u> 138	▲ 189	
Sodium	ppm	6	1 0	
Potassium	ppm	12	2 1	
VOLVO				
WEAR M	TETALS			
Iron	ppm	496	□262	
Copper	ppm	2	- <1	
Lead	ppm	<1	0	
Tin	ppm	 ■ <1	0	
Aluminum	ppm	<u>31</u>	49	
Chromium	ppm	6	1 4	
Molybdenum	ppm	5	0	
Nickel	ppm	<1	<1	
Titanium	ppm	2	3	
Silver	ppm	<1	0	
Manganese	ppm	4	4	
Vanadium	ppm	<1	0	
	•			
ADDITIV	IEC			
_				
Calcium	ppm	150	126	
Magnesium	ppm	46	16	
Zinc	ppm	79	14	
Phosphorus	ppm	789	417	
Barium	ppm	0	2	
Boron	ppm	138	<1	

ALTA EQUIPMENT

5985 COURT STREET ROAD SYRACUSE, NY US 13206 Contact: JIM STRIGLE JIM.STRIGLE@ALTG.COM T: (315)437-2611 F: (315)434-9471

Diagnosis

We advise that you check all areas where dirt can enter the system. Resample at the next service interval to monitor. All component wear rates are normal. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0142Unique No:9516125Signed:Doug BogartReport Date:25 May 2021



CONSTRUCTION EQUIPMENT





