

CONSTRUCTION EQUIPMENT 567435 APTIM VOLVO A35G 340070 - DROP BOX



Sample No: VCP416004

Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5

Job No: 567435 APTIM

SAMPLE	INFORMATION				
Sample Number	_	VCP416004	VCP411064	VCP385129	
Sample Date		26 Jun 2023	19 Apr 2023	08 Nov 2022	
Machine Hours		8469	7985	6869	
Oil Hours		8469	2000	2000	
Oil Changed		Changed	Not Changd	Not Changd	
Sample Status		ABNORMAL	ABNORMAL	NORMAL	
OIL CONI	NITION				
Visc @ 40°C	cSt	<u>▲</u> 65.6	<u></u> ▲ 61.8	282	
VISC @ 40 C	CSL	<u> </u>	01.0	<u> </u>	
VOLVO					
CONTAM	INATION				
Silicon	ppm	109	△ 107	1 6	
Sodium	ppm	■7	6	- <1	
Potassium	ppm	■8	9	0	
WEAR M	ETALS				
Iron	ppm	△ 637	<u></u> ▲ 622	6 9	
Copper	ppm	■ 5	4	5	
Lead	ppm		1	0	
Tin	ppm	■ 0	- <1	0	
Aluminum	ppm	<u>^</u> 50	4 8	7	
Chromium	ppm	■ 7	7	< 1	
Molybdenum	ppm	■10	1 0	6	
Nickel	ppm	■ <1	1	1	
Titanium	ppm	<1	<1	<1	
Silver	ppm	0	0	0	
Manganese	ppm	■11	1 1	_1	
Vanadium	ppm	0	0	0	
VOLVO					
ADDITIV	ES				
Calcium	ppm	121	1 113	129	
Magnesium	ppm	■35	3 6	2 9	
Zinc	ppm	391	368	■84	
Phosphorus	ppm	■1395	1306	■916	
Barium	ppm	0	0	0	
Boron	ppm	■87	■86	1 59	



ALTA EQUIPMENT/FLAGLER CONSTRUCTION EQUIPMENT LLC
8418 PALM RIVER ROAD
TAMPA, FL
US 33619
Contact: JOHN FARDELLA
JFARDELLA@ALTAEQUIPFL.COM
T: (813)630-0077
F: (813)630-2233

Diagnosis

We advise that you check all areas where dirt can enter the system. The oil change at the time of sampling has been noted. Resample at the next service interval to monitor. Gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The oil viscosity is lower than normal. Confirm oil type.

Depot:VOLVO0093Unique No:10573587Signed:Don BaldridgeReport Date:27 Jul 2023



CONSTRUCTION EQUIPMENT





