

## **CONSTRUCTION EQUIPMENT**

580154 STONE VOLVO EC350 314509 - HYDRAULIC SYSTEM

Sample No: VCP413217

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

**Job No:** 580154 STONE

VOLVO	NFORMATION			
	NEUKMATIUN		 	
Sample Number		VCP413217	 	
Sample Date		07 Aug 2023	 	
Machine Hours		608	 	
Oil Hours		608	 	
Oil Changed		Not Changd	 	
Sample Status		ABNORMAL	 	
OIL CONDI	TION			
Visc @ 40°C		= 44.6	 	
	cSt	<b>41.6</b>	 	
Acid Number (AN)	mg KOH/g	■ 0.52	 	
VOLVO				
CONTAMII	NATION			
Particles >4µm		<u> </u>	 	
Particles > 6µm		△ 39103	 	
Particles > 14µm		▲ 7955	 	
ISO 4406:1999 (c)		24/22/20	 	
Silicon	nnm	<b>□</b> 2	 	
Sodium	ppm	<b>■</b> 2	 	
Potassium	ppm	<b>1</b>	 	
	ppm	·	 	
VOLVO				
<b>WEAR ME</b>	TALS			
Iron	ppm	<b>2</b>	 	
Copper	ppm	<b>14</b>	 	
Lead	ppm	<b>■&lt;1</b>	 	
Tin	ppm	■0	 	
Aluminum	ppm	<b>■&lt;1</b>	 	
Chromium	ppm	<1	 	
Molybdenum	ppm	■0	 	
Nickel	ppm	■0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	<b>0</b>	 	
Vanadium	ppm	0	 	
		_		
VOLVO	_			
ADDITIVE	7			
Calcium	ppm	<b>■87</b>	 	
Magnesium	ppm	<b>■&lt;1</b>	 	
	-			



ALTA EQUIPMENT COMPANY - METRO WEST 56195 PONTIAC TRAIL NEW HUDSON, MI US 48165 Contact: PAUL ELZERMAN paul.elzerman@altaequipment.com T: (248)356-5200 F: (248)356-2029

## Diagnosis

We advise that you perform a filter service, and use off-line filtration to improve the cleanliness of the system fluid. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of particulates (2 to 100 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:VOLVO2990Unique No:10604744Signed:Wes DavisReport Date:16 Aug 2023

**538** 

**412** 

**■**0

ppm

ppm

ppm

ppm

Zinc

Barium

Boron

Phosphorus



## **CONSTRUCTION EQUIPMENT**





## GRAPHS

