

CONSTRUCTION EQUIPMENT VOLVO A40G 352973 - HYDRAULIC SYSTEM



Sample No: VCP421325

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No:

VOLVO				
SAMPLE II	NFORMATION			
Sample Number	-	VCP421325	 	
Sample Date		04 Aug 2023	 	
Machine Hours		1903	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
VOLVO				
OIL CONDI	TION			
Visc @ 40°C	cSt	46.8	 	
Acid Number (AN)		0.36	 	
ricia rumber (rirt)	mg Ron, g	0.50		
VOLVO	MATION			
CONTAMIN	NATIUN			
Particles >4µm		6023	 	
Particles >6µm		■830	 	
Particles >14µm		■29	 	
ISO 4406:1999 (c)		20/17/12	 	
Silicon	ppm	11	 	
Sodium	ppm	■0	 	
Potassium	ppm	1	 	
VOLVO				
WEAR ME	TALS			
Iron	ppm	■ 9	 	
Copper	ppm	■ 3	 	
Lead	ppm	3	 	
Tin	ppm	■<1	 	
Aluminum	ppm	2	 	
Chromium	ppm	■<1	 	
Molybdenum	ppm	0	 	
Nickel	ppm	■ 0	 	
Titanium	ppm	<1	 	
Silver	ppm	0	 	
Manganese	ppm	0	 	
Vanadium	ppm	0	 	
VOLVO				
ADDITIVE:	2			
Calcium	ppm	101	 	
Magnesium	ppm	1	 	
Zinc	ppm	448	 	
Phosphorus	ppm	■333	 	
Barium	ppm	 <1	 	
Boron	ppm	■ 0	 	



ALTA EQUIPMENT COMPANY

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK tlark@altaequipfl.com

T:

F: (239)481-3302

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:VOLVO0090Unique No:10605998Signed:Wes DavisReport Date:17 Aug 2023



CONSTRUCTION EQUIPMENT





GRAPHS

