

CONSTRUCTION EQUIPMENT X47616 TADANO GR1600XL FE5397 - DIESEL ENGINE



Sample No: VCP415863

Oil Type: DIESEL ENGINE OIL SAE 15W40

Job No: X47616

SAMPLE IN	NFORMATION			
Sample Number	-	VCP415863	 	
Sample Date		06 Sep 2023	 	
Machine Hours		1886	 	
Oil Hours		0	 	
Oil Changed		N/A	 	
Sample Status		ABNORMAL	 	
VOLVO	TION			
OIL CONDI.				
Visc @ 100°C	cSt	13.2	 	
Base Number (BN)	mg KOH/g	4.8	 	
Oxidation (PA)	%	89	 	
CONTAMIN	IATION			
Soot %	%	0.3	 	
Nitration (PA)	%	94		
Sulfation (PA)	%	66	 	
	%	NEG		
Glycol Fuel	%	<1.0	 	
Silicon		< 1.0 <u>^</u> 50	 	
Sodium	ppm	6	 	
Potassium	ppm	■0 ■11	 	
Potassium	ppm		 	
VOLVO				
WEAR ME	TALS			
Iron	ppm	61	 	
Copper	ppm	180	 	
Lead	ppm	0	 	
Tin	ppm	-<1	 	
Aluminum	ppm	1 4	 	
Chromium	ppm	■3	 	
Molybdenum	ppm	■ 59	 	
Nickel	ppm	■0	 	
Titanium	ppm	□ 0	 	
Silver	ppm	■ 0	 	
Manganese	ppm	6	 	
Vanadium	ppm	0	 	



SCOTT EQUIPMENT COMPANY LLC - Lake Charles
PO BOX 16955
LAKE CHARLES, LA
US 70616
Contact: FRED RACCA
fracca@scottcompanies.com
T: (337)433-9811
F: (337)433-6623

Diagnosis

We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. Resample at the next service interval to monitor.All component wear rates are normal. Elemental levels of silicon (Si) and aluminum (Al) indicate aluminasilicate (coarse dirt) ingress. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO6244Unique No:10644703Signed:Don BaldridgeReport Date:14 Sep 2023

1839

■ 388 ■ 1202

915

■9

24

ADDITIVES

ppm

ppm

ppm

ppm

ppm

ppm

Calcium

Zinc

Barium

Boron

Magnesium

Phosphorus



CONSTRUCTION EQUIPMENT





