

CONSTRUCTION EQUIPMENT VOLVO A30G 752996 - BOGIE/CENTER AXLE



Sample No: VCP413313

Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5

Job No:

CVMDIE	INFORMATIO	1		
_	INFURMATIU			
Sample Number		VCP413313	 	
Sample Date		06 Sep 2023	 	
Machine Hours		1177	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		ATTENTION	 	
OIL CON	DITION			
Visc @ 40°C	cSt	<u>▲</u> 86.3	 	
VISC @ 40 C	CSL	<u> </u>	 	
VOLVO				
CONTAN	MINATION			
Silicon	ppm	6	 	
Sodium	ppm	1	 	
Potassium	ppm	■ 6	 	
	le le			
VOLVO	AFTAL C			
WEAR N	NE I ALS			
Iron	ppm	269	 	
Copper	ppm	10	 	
Lead	ppm	■<1	 	
Tin	ppm	■<1	 	
Aluminum	ppm	0	 	
Chromium	ppm	■ 5	 	
Molybdenum	ppm	6	 	
Nickel	ppm	■ 3	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	11	 	
Vanadium	ppm	0	 	
ADDITIV	/ES			
Calcium	ppm	1068	 	
Magnesium	ppm	5	 	
Zinc	ppm	<u></u> 438	 	
Phosphorus	ppm	<u> </u>	 	
Barium	ppm	■0	 	
Boron	ppm	<u>^</u> 267	 	
•	PPIII			



ALTA EQUIPMENT/FLAGLER EQUIPMENT LLC
9601 BOGGY CREEK RD
ORLANDO, FL
US 32824
Contact: Robert LaPlante
robert.laplante@altg.com
T: (407)508-9736
F: (407)659-8720

Diagnosis

No corrective action is recommended at this time. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The oil viscosity is lower than normal. Additive levels indicate the addition of a different brand, or type of oil. Confirm oil type.

Depot:VOLVO0096Unique No:10646478Signed:Jonathan HesterReport Date:18 Sep 2023



CONSTRUCTION EQUIPMENT





