

## **CONSTRUCTION EQUIPMENT**

X47299 TADANO GR 1600XL FE5323 - HYDRAULIC SYSTEM



Oil Type: VOLVO SUPER HYDRAULIC OIL 46

**Job No:** X47299

VOLVO					
SAMPLE INFORMATION					
Sample Number		VCP416484			
Sample Date		13 Sep 2023			
Machine Hours		4629			
Oil Hours		0			
Oil Changed		N/A			
Sample Status		ABNORMAL			
OIL CONDITION					
Visc @ 40°C	cSt	<b>▲</b> 34.22			
Acid Number (AN	mg KOH/g	■ 0.21			
CONTAMINATION					
	INATION				
Particles >4µm		<u>^</u> 22805			
Particles > 6µm		<u>▲</u> 5501			
Particles > 14µm		<u>^</u> 270			
ISO 4406:1999 (c)		22/20/15			
Silicon	ppm	<b>■</b> <1			
Sodium	ppm	<b>2</b>			
Potassium	ppm	■ 0			
VOLVO					
WEAR METALS					
Iron	ppm	<b>1</b>			
Copper	ppm	<b>-</b> <1			
Lead	ppm	<b>0</b>			
Tin	ppm	<b>■</b> 0			
Aluminum	ppm	<b>0</b>			
Chromium	ppm	<b>■</b> <1			
Molybdenum	ppm	<b>0</b>			
Nickel	ppm	<b>0</b>			
Titanium	ppm	0			
Silver	ppm	0			
Manganese	ppm	<b>■&lt;1</b>			
Vanadium	ppm	0			
ADDITIVES					
Calcium	ppm	<b>2</b>			
Magnesium	ppm	<b>1</b>			
agiicsiaiii	PPIII				



SCOTT EQUIPMENT COMPANY LLC - Lake Charles
PO BOX 16955
LAKE CHARLES, LA
US 70616
Contact: TINA LEDOUX
tledoux@scottcompanies.com
T: (337)433-9811

## Diagnosis

F: (318)433-6623

We recommend you service the filters on this component. Resample at the next service interval to monitor.All component wear rates are normal. There is a high amount of particulates present in the oil. Viscosity of sample indicates oil is within ISO 32 range, advise investigate. Confirm oil type. The AN level is acceptable for this fluid.

Depot:VOLVO6244Unique No:10657638Signed:Jonathan HesterReport Date:27 Sep 2023

**3** 

**0** 

**0** 

**585** 

ppm

ppm

ppm

ppm

Zinc

Barium

Boron

Phosphorus



## **CONSTRUCTION EQUIPMENT**





## GRAPHS

