

# CONSTRUCTION EQUIPMENT 9569 VOLVO A30G 742602 - FRONT AXLE



Sample No: VCP413773

Oil Type: VOLVO SUPER GEAR OIL 75W-80-GO102

**Job No:** 9569

| SAMPLI        | E INFORMATION |             |               |      |
|---------------|---------------|-------------|---------------|------|
| Sample Number |               | VCP413773   | VCP291527     | <br> |
| Sample Date   |               | 11 Sep 2023 | 24 Feb 2021   | <br> |
| Machine Hours |               | 3908        | 902           | <br> |
| Oil Hours     |               | 0           | 0             | <br> |
| Oil Changed   |               | Changed     | Changed       | <br> |
| Sample Status |               | NORMAL      | NORMAL        | <br> |
|               |               |             |               |      |
| OIL CON       | IDITION       |             |               |      |
|               |               | _           |               |      |
| Visc @ 40°C   | cSt           | <b>46.2</b> | <b>□</b> 56.8 | <br> |
| VOLVO         |               |             |               |      |
| CONTAI        | MINATION      |             |               |      |
| Silicon       | ppm           | <b>2</b>    | <b>4</b>      | <br> |
| Sodium        | ppm           | <u></u> 4   | 2             | <br> |
| Potassium     | ppm           | <b>■</b> <1 | <b>1</b> 4    | <br> |
|               | ρρ            |             |               |      |
| VOLVO         | AFTAL C       |             |               |      |
| WEAR          | METALS        |             | _             |      |
| Iron          | ppm           | <b>■78</b>  | ■238          | <br> |
| Copper        | ppm           | <b>15</b>   | ■25           | <br> |
| Lead          | ppm           | ■0          | <b>-</b> <1   | <br> |
| Tin           | ppm           | <b>■</b> <1 | <b>1</b>      | <br> |
| Aluminum      | ppm           | <b>■</b> <1 | <b>0</b>      | <br> |
| Chromium      | ppm           | <b></b>     | <b>5</b>      | <br> |
| Molybdenum    | ppm           | <b></b>     | 14            | <br> |
| Nickel        | ppm           | <b></b>     | <b>3</b>      | <br> |
| Titanium      | ppm           | 0           | <1            | <br> |
| Silver        | ppm           | 0           | 0             | <br> |
| Manganese     | ppm           | <b>2</b>    | 13            | <br> |
| Vanadium      | ppm           | <1          | 0             | <br> |
| VOLVO         |               |             |               |      |
| ADDITIV       | VES           |             |               |      |
| Calcium       | ppm           | <b>462</b>  | 782           | <br> |
| Magnesium     | ppm           | <b>0</b>    | 1             | <br> |
| Zinc          | ppm           | <b>251</b>  | 344           | <br> |
| Phosphorus    | ppm           | <b>2130</b> | 1436          | <br> |
| Barium        | ppm           | <u> </u>    | 0             | <br> |
| Boron         | ppm           | <b>214</b>  | 173           | <br> |
|               |               |             |               |      |



#### PLEASANT EXCAVATING COMPANY INC

24024 FREDERICK ROAD CLARKSBURG, MD US 20871 Contact: H TRENT HTRENT@PLEASANTS.ORG T: (301)252-5635 F:

### Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:PLECLAUnique No:10657924Signed:Wes DavisReport Date:21 Sep 2023

Contact/Location: H TRENT - PLECLA



## **CONSTRUCTION EQUIPMENT**





