

CONSTRUCTION EQUIPMENT 9569 VOLVO A30G 742602 - REAR AXLE



Sample No: VCP426164

Oil Type: VOLVO SUPER GEAR OIL 75W-80-GO102

Job No: 9569

VOLVO				
SAMPLE	E INFORMATION			
Sample Number	_	VCP426164	VCP291519	
Sample Date		11 Sep 2023	24 Feb 2021	
Machine Hours		3908	902	
Oil Hours		0	0	
Oil Changed		Changed	Changed	
Sample Status		NORMAL	NORMAL	
OIL CON	IDITION			
			_	
Visc @ 40°C	cSt	47.3	62.0	
VOLVO				
CONTAN	MINATION			
Silicon	ppm	3	4	
Sodium	ppm	4	1 4	
Potassium	ppm	2	1 4	
	le le			
WEAR N	AFTAI C			
_		=00	= 220	<u> </u>
Iron	ppm	■80	□ 228	
Copper	ppm	1 4	1 7	
Lead	ppm	■ 0	<1	
Aluminum	ppm	_		
	ppm	<1	0	
Chromium	ppm	□ <1	□ 6 12	
Molybdenum Nickel	ppm	■<1 ■<1	3	
Titanium	ppm	0	<1	
Silver	ppm	0	<1	
Manganese	ppm	■2	19	
Vanadium	ppm	0	0	
Variadialii	ppiii	V	U	
VOLVO	upe .			
ADDITIV	VEZ			
Calcium	ppm	■359	85	
Magnesium	ppm	1	<1	
Zinc	ppm	210	20	
Phosphorus	ppm	2189	1393	
Barium	ppm	■0	0	
Boron	ppm	279	202	



PLEASANT EXCAVATING COMPANY INC

24024 FREDERICK ROAD CLARKSBURG, MD US 20871 Contact: H TRENT HTRENT@PLEASANTS.ORG T: (301)252-5635 F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:PLECLAUnique No:10657926Signed:Wes DavisReport Date:21 Sep 2023

Contact/Location: H TRENT - PLECLA



CONSTRUCTION EQUIPMENT





