

CONSTRUCTION EQUIPMENT 9570 VOLVO A30G 742606 - FRONT AXLE



Sample No: VCP423097

Oil Type: VOLVO SUPER GEAR OIL 75W-80-GO102

Job No: 9570

SAMPLE	E INFORMATIO	N		
Sample Number	_	VCP423097	VCP294845	
Sample Date		14 Sep 2023	19 Nov 2020	
Machine Hours		4157	868	
Oil Hours		0	0	
Oil Changed		Changed	Changed	
Sample Status		NORMAL	NORMAL	
VOLVO	DITION			
OIL CON	MILIAN			
Visc @ 40°C	cSt	45.7	56.7	
CONTAN	MINATION			
Silicon	ppm	4	1	
Sodium	ppm	1 4	2	
Potassium	ppm	3	1 4	
rotassium	ррпп		4	
VOLVO				
WEAR N	METALS			
Iron	ppm	218	□173	
Copper	ppm	■20	■20	
Lead	ppm	0	0	
Tin	ppm	■<1	- <1	
Aluminum	ppm	-<1	 <1	
Chromium	ppm	■ 3	4	
Molybdenum	ppm	2	6	
Nickel	ppm	2	3	
Titanium	ppm	0	<1	
Silver	ppm	0	<1	
Manganese	ppm	6	13	
Vanadium	ppm	<1	0	
VOLVO				
ADDITIV	VES			
Calcium	ppm	1328	749	
Magnesium	ppm	■5	2	
Zinc	ppm	599	326	
Phosphorus	ppm	■ 1802	1403	
Barium	ppm	0	1	
Boron	ppm	235	179	
201011	PPIII		175	



PLEASANT EXCAVATING COMPANY INC

24024 FREDERICK ROAD CLARKSBURG, MD US 20871 Contact: H TRENT HTRENT@PLEASANTS.ORG T: (301)252-5635 F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:PLECLAUnique No:10657929Signed:Wes DavisReport Date:21 Sep 2023

Contact/Location: H TRENT - PLECLA



CONSTRUCTION EQUIPMENT





