

CONSTRUCTION EQUIPMENT

606215 DIPRO KOMATSU WA480 A48036 - HYDRAULIC SYSTEM

Sample No: VCP431154

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No: 606215 DIPRO

VOLVO	INFORMATION			
_	INFURMATION			
Sample Number		VCP431154	 	
Sample Date		21 Sep 2023	 	
Machine Hours		8231	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		ABNORMAL	 	
OIL CON	NITION			
_	cSt	= 45.4		
Visc @ 40°C		45.4		
Acid Number (AN	N) mg KOH/g	■ 0.76	 	
VOLVO				
CONTAN	MINATION			
Particles >4µm		<u>^</u> 25030	 	
Particles > 6µm		△ 3965	 	
Particles > 14µm		■38	 	
ISO 4406:1999 (c)	22/19/12	 	
Silicon	ppm	4	 	
Sodium	ppm	2	 	
Potassium	ppm	0	 	
Otassiani	PPIII			
VOLVO				
WEAR N	VF I ALS			
Iron	ppm	13	 	
Copper	ppm	■3	 	
Lead	ppm	0	 	
Tin	ppm	■ <1	 	
Aluminum	ppm	■ <1	 	
Chromium	ppm	1	 	
Molybdenum	ppm	6	 	
Nickel	ppm	■ 0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	■<1	 	
Vanadium	ppm	0	 	
ADDITIV	IEC			
_				
Calcium	ppm	2220	 	
Magnesium	ppm	■34	 	
Zinc	ppm	785	 	
Phosphorus	ppm	641	 	

ALTA EQUIPMENT COMPANY - METRO WEST

56195 PONTIAC TRAIL NEW HUDSON, MI US 48165 Contact: PAUL CONZ paul.conz@altg.com T: (313)348-8861 F: (248)356-2029

Diagnosis

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.All component wear rates are normal. There is a high amount of silt (particulates < 14 microns in size) present in the oil. The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

Depot:VOLVO2990Unique No:10668724Signed:Don BaldridgeReport Date:28 Sep 2023

0

ppm

ppm

Barium

Boron



CONSTRUCTION EQUIPMENT





GRAPHS

