

CONSTRUCTION EQUIPMENT 9640 VOLVO A25G 752013 - REAR AXLE



Sample No: VCP413686

Oil Type: VOLVO SUPER GEAR OIL 75W-80-GO102

Job No: 9640

CAMPI	E INFORMATION	l e			
			VCD202202		_
Sample Number		VCP413686	VCP282302		
Sample Date		16 Sep 2023	02 Oct 2020		
Machine Hours		4616	463		
Oil Hours		0	0		
Oil Changed		Changed	Changed		
Sample Status		NORMAL	NORMAL		
VOLVO					
OIL CON	IDITION				
Visc @ 40°C	cSt	49.1	61.4		
	COC		01.1		
VOLVO					
CONTAI	MINATION				
Silicon	ppm	4	4		
Sodium	ppm	3	4		
Potassium	ppm	4	<u> </u>		
	I I	_			
WEAR	METALS				
Iron	ppm	□204	□304		
Copper	ppm	■18	1 8		
Lead	ppm	■0	0		
Tin	ppm	■<1	<1		
Aluminum	ppm	0	0		
Chromium	ppm	3	1 6		
Molybdenum	ppm	1	6		
Nickel	ppm	2	3		
Titanium	ppm	0	<1		
Silver	ррт	0	0		
Manganese	ppm	■ 5	19		
Vanadium	ррт	0	0		
variacium	ppili	U U	U	-2-	
VOLVO					
ADDITIV	VES				
Calcium	ppm	908	357		
Magnesium	ppm	3	<1		
Zinc	ppm	416	138		
Phosphorus	ppm	1861	1389		
Barium	ppm	■0	<1		
Boron	ppm	209	207		
_ 3. 0	PPIII				



MCCLUNG-LOGAN EQUIPMENT CO - BALTIMORE
4601 WASHINGTON BOULEVARD
BALTIMORE, MD
US 21227
Contact: MARK CIULLA
mciulla@mcclung-logan.com
T: (410)242-6500
F: (410)242-7835

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0150Unique No:10695819Signed:Don BaldridgeReport Date:17 Oct 2023



CONSTRUCTION EQUIPMENT





