

Sample No: VCP425214

Oil Type: MOBIL HYDRAULIC OIL AW 46

Job No: W02007586

VOLVO				
SAMPLE	INFORMATION			
Sample Number	-	VCP425214	 	
Sample Date		03 Oct 2023	 	
Machine Hours		1989	 	
Oil Hours		2000	 	
Oil Changed		Changed	 	
Sample Status		NORMAL	 	
OIL CON	DITION			
	<u>.</u>		<u> </u>	_
Visc @ 40°C	cSt	40.9	 	
Acid Number (AN	I) mg KOH/g	0.57	 	
VOLVO				
CONTAN	IINATION			
Particles >4µm		■892	 	
Particles >6µm		146	 	
Particles > 14µm		■17	 	
ISO 4406:1999 (c))	17/14/11	 	
Silicon	ppm	4	 	
Sodium	ppm	□ <1	 	
Potassium	ppm	■ <1	 	
	r r	_		
VOLVO	IETAL C			
WEAR M	IE I ALS			
Iron	ppm	■ 3	 	
Copper	ppm	■21	 	
Lead	ppm	■<1	 	
Tin	ppm	■0	 	
Aluminum	ppm	■<1	 	
Chromium	ppm	■<1	 	
Molybdenum	ppm	■ <1	 	
Nickel	ppm	■0	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	■ <1	 	
Vanadium	ppm	0	 	
VOLVO			 	
ADDITIV	/ES			
Calcium	ppm	129	 	
Magnesium		0	 	
Zinc	ppm	488	 	
Phosphorus	ppm		 	
	ppm	■389	 	



MCCLUNG-LOGAN EQUIPMENT CO - MANASSAS 8450 QUARRY ROAD MANASSAS, VA US 20110 Contact: MIKE MAYHUGH MMAYHUGH@MCCLUNG-LOGAN.COM T: (703)393-7344 F: (703)393-7844

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:VOLVO0002Unique No:10696848Signed:Don BaldridgeReport Date:17 Oct 2023

0

ppm

ppm

Barium

Boron



CONSTRUCTION EQUIPMENT





GRAPHS

