

## CONSTRUCTION EQUIPMENT VOLVO A25G VCP 413192 (S/N NOT GIVEN) - REAR AXLE



Sample No: VCP432751

Oil Type: VOLVO PREMIUM GEAR OIL 85W-140 GL-5

Job No:

VOLVO	INFORMATIO	V		
	. INFURMATIU			<u> </u>
Sample Number		VCP432751	 	
Sample Date		24 Oct 2023	 	
Machine Hours		4800	 	
Oil Hours		0	 	
Oil Changed		Changed	 	
Sample Status		ABNORMAL	 	
OIL CON	DITION			
Visc @ 40°C		=122	 	
VISC @ 40°C	cSt	<b>122</b>	 	
VOLVO				
CONTAN	INATION			
Silicon	ppm	<u>^</u> 64	 	
Sodium	ppm	<b>2</b>	 	
Potassium	ppm	<b>2</b>	 	
rotassiam	ррпп			
VOLVO				
WEAR M	<b>IETALS</b>			
Iron	ppm	<b>224</b>	 	
Copper	ppm	<b>■28</b>	 	
Lead	ppm	<b>0</b>	 	
Tin	ppm	<b>1</b>	 	
Aluminum	ppm	<u>^</u> 8	 	
Chromium	ppm	<b>■</b> 3	 	
Molybdenum	ppm	<u> </u>	 	
Nickel	ppm	2	 	
Titanium	ppm	<1	 	
Silver	ppm	0	 	
Manganese	ppm	<b>3</b>	 	
Vanadium	ppm	0	 	
VOLVO	IFC		 	
ADDITIV	ES			
Calcium	ppm	<b>109</b>	 	
Magnesium	ppm	<b>1</b> 5	 	
Zinc	ppm	■58	 	
Phosphorus	ppm	■995	 	
Barium	ppm	<b>0</b>	 	
Boron	ppm	<b>171</b>	 	



ALTA EQUIPMENT/FLAGLER EQUIPMENT LLC 9601 BOGGY CREEK RD ORLANDO, FL US 32824 Contact: Robert LaPlante robert.laplante@altg.com T: (407)508-9736

## Diagnosis

F: (407)659-8720

We advise that you check all areas where dirt can enter the system. The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.All component wear rates are normal. Elemental levels of silicon (Si) and aluminum (Al) indicate aluminasilicate (coarse dirt) ingress. Confirm oil type. The condition of the oil is acceptable for the time in service.

Depot:VOLVO0096Unique No:10712164Signed:Don BaldridgeReport Date:27 Oct 2023



## **CONSTRUCTION EQUIPMENT**





