

CONSTRUCTION EQUIPMENT W14891 VOLVO A40G 353432 - FRONT AXLE



Sample No: VCP441675

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: W14891

SAMPLE	E INFORMATIO	N		
Sample Number		VCP441675	 	
Sample Date		27 Oct 2023	 	
Machine Hours		954	 	
Oil Hours		1000	 	
Oil Changed		Changed	 	
Sample Status		ATTENTION	 	
VOLVO	DITION			
OIL CON				
Visc @ 40°C	cSt	<u>▲</u> 52.4	 	
VOLVO				
CONTAN	MINATION			
Silicon		4	 	
Sodium	ppm	3	 	
Potassium	ppm	■ 6	 	
rotassium	ppm			
VOLVO				
WEAR N	METALS			
Iron	ppm	149	 	
Copper	ppm	2	 	
Lead	ppm	■<1	 	
Tin	ppm	■<1	 	
Aluminum	ppm	■<1	 	
Chromium	ppm	■ 2	 	
Molybdenum	ppm	■2	 	
Nickel	ppm	■<1	 	
Titanium	ppm	0	 	
Silver	ppm	0	 	
Manganese	ppm	■8	 	
Vanadium	ppm	0	 	
VOLVO			 	
ADDITIV	/ES			
Calcium	ppm	7	 	
Magnesium	ppm	1 5	 	
Zinc	ppm	2	 	
Phosphorus	ppm	2456	 	
Barium	ppm	■0	 	
Boron	ppm	239	 	
201011	PPIII			



HOUSBY HEAVY EQUIPMENT, LLC

4410 SE 4 MILE DR ANKENY, IA US 50021 Contact: RANDY VANDERLEEST rvanderleest@housby.com T: F: (515)964-2865

Diagnosis

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The oil viscosity is lower than normal. Confirm oil type.

Depot:VOLVO0080Unique No:10723069Signed:Don BaldridgeReport Date:01 Nov 2023



CONSTRUCTION EQUIPMENT





GRAPHS

