

CONSTRUCTION EQUIPMENT

WASTE CONN ST PETE VOLVO L35GS 3424291 - HYDRAULIC SYST

Sample No: VCP365198

Oil Type: AW HYDRAULIC OIL ISO 46

Job No: WASTE CONN ST PETE

SAMPLE IN	NFORMATION			
Sample Number		VCP365198	 	
Sample Date		05 Oct 2023		
Machine Hours		12010	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		ABNORMAL		
Sample Status		ADNORMAL		
VOLVO				
OIL CONDI	TION			
Visc @ 40°C	cSt	42.6	 	
Acid Number (AN)	mg KOH/g	0.48	 	
CONTAMIN	IATION			
_	IATIUN			
Particles >4µm		16896	 	
Particles >6µm		6667	 	
Particles >14µm		<u>▲</u> 582	 	
ISO 4406:1999 (c)		21/20/16	 	
Silicon	ppm	1	 	
Sodium	ppm	■ <1	 	
Potassium	ppm	■ <1	 	
VOLVO				
WEAR ME	ZIAT			
Iron		1 3	 	
	ppm	1		
Copper Lead	ppm	0	 	
Tin	ppm	0	 	
Aluminum	ppm	3	 	
Chromium	ppm	0	 	
Molybdenum	ppm	_	 	
	ppm	0	 	
Nickel Titanium	ppm	0	 	
Silver	ppm	0	 	
	ppm	0	 	
Manganese	ppm	0	 	
Vanadium	ppm	U	 	
VOLVO			 	
ADDITIVE!	<u> </u>			
Calcium	ppm	79	 	
Magnesium	ppm	7	 	
Zinc	ppm	■440	 	
-	In law or a			



ALTA EQUIPMENT/FLAGLER CONSTRUCTION EQUIPMENT LLC
8418 PALM RIVER ROAD
TAMPA, FL
US 33619
Contact: KENNY HANEY
khaney@flaglerce.com
T: (813)630-0077
F: (813)630-2233

Diagnosis

We advise that you perform a filter service, and use off-line filtration to improve the cleanliness of the system fluid. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of particulates (2 to 100 microns in size) present in the oil. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

Depot:VOLVO0093Unique No:10723879Signed:Wes DavisReport Date:02 Nov 2023

337

0

1

ppm

ppm

ppm

Phosphorus

Barium

Boron



CONSTRUCTION EQUIPMENT





GRAPHS

