

Sample No: VCP432922

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No: 632549 ASH GROVE

VOLVO				
	INFORMATION			
Sample Number	-	VCP432922	 	
Sample Date		02 Nov 2023	 	
Machine Hours		12219	 	
Oil Hours		0	 	
Oil Changed		Not Changd	 	
Sample Status		ATTENTION	 	
OIL CON	DITION			
			 <u>.</u>	
Visc @ 40°C	cSt	41.5	 	
Acid Number (AN	N) mg KOH/g	■ 0.37	 	
VOLVO				
CONTAN	MINATION			
Particles >4µm		△ 5366	 	
Particles >6µm		■1104	 	
Particles > 14µm		■60	 	
ISO 4406:1999 (c)	20/17/13	 	
Silicon	ppm	■3	 	
Sodium	ppm	■3	 	
Potassium	ppm	■<1	 	
		_		
VOLVO	AETAL C			
WEAR N	JE I HEZ			
Iron	ppm	■3	 	
Copper	ppm	1	 	
Lead	ppm	1	 	
Tin	ppm	■0	 	
Aluminum	ppm	■ <1	 	
Chromium	ppm	■ <1	 	
Molybdenum	ppm	■0	 	
Nickel	ppm	■ <1	 	
Titanium	ppm	0	 	
Silver	nnm	0		
	ppm			
Manganese	ppm	■ <1	 	
Manganese Vanadium				
Vanadium	ppm	■ <1		
Vanadium	ppm ppm	■ <1		
Vanadium	ppm ppm			
Vanadium ADDITIV	ppm ppm	<1 0	 	
Vanadium ADDITIV Calcium Magnesium	ppm ppm		 	
Vanadium ADDITIV	ppm ppm	<1 0	 	



ALTA EQUIPMENT/FLAGLER EQUIPMENT LLC 9601 BOGGY CREEK RD ORLANDO, FL US 32824

Contact: Robert LaPlante robert.laplante@altg.com T: (407)508-9736

F: (407)659-8720

Diagnosis

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. All component wear rates are normal. There is a light amount of silt (particulates < 14 microns in size) present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:VOLVO0096Unique No:10728815Signed:Wes DavisReport Date:08 Nov 2023

ppm

ppm

0

Barium

Boron



CONSTRUCTION EQUIPMENT





GRAPHS

