



CONSTRUCTION EQUIPMENT

368 JOHN DEERE 814867 - REAR LEFT FINAL DRIVE



Sample No: VCP408577
Oil Type: DRYDENE LIMITED SLIP GEAR 80W90
Job No: 368



SAMPLE INFORMATION

Sample Number	VCP408577	---	---	---
Sample Date	19 Oct 2023	---	---	---
Machine Hours	4805	---	---	---
Oil Hours	1000	---	---	---
Oil Changed	Changed	---	---	---
Sample Status	ABNORMAL	---	---	---

TOTAL DEVELOPMENT SOLUTIONS LLC
 7805 PROGRESS CT
 GAINESVILLE, VA
 US 20155
 Contact: JOE SEALE
 jseale@totaldevelopmentsolutions.com
 T: (703)222-0497
 F: (703)753-4586



OIL CONDITION

Visc @ 40°C	cSt	█ 143	---	---	---
-------------	-----	-------	-----	-----	-----



CONTAMINATION

Silicon	ppm	▲ 142	---	---	---
Sodium	ppm	█ 4	---	---	---
Potassium	ppm	█ 5	---	---	---



WEAR METALS

Iron	ppm	█ 281	---	---	---
Copper	ppm	█ 0	---	---	---
Lead	ppm	█ 0	---	---	---
Tin	ppm	█ 0	---	---	---
Aluminum	ppm	▲ 58	---	---	---
Chromium	ppm	█ 2	---	---	---
Molybdenum	ppm	█ 3	---	---	---
Nickel	ppm	█ 1	---	---	---
Titanium	ppm	4	---	---	---
Silver	ppm	0	---	---	---
Manganese	ppm	4	---	---	---
Vanadium	ppm	<1	---	---	---



ADDITIVES

Calcium	ppm	█ 71	---	---	---
Magnesium	ppm	█ 38	---	---	---
Zinc	ppm	█ 74	---	---	---
Phosphorus	ppm	█ 706	---	---	---
Barium	ppm	█ 0	---	---	---
Boron	ppm	█ 45	---	---	---

Diagnosis

We advise that you check all areas where dirt can enter the system. The oil change at the time of sampling has been noted. Resample at the next service interval to monitor. All component wear rates are normal. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The condition of the oil is acceptable for the time in service.

Depot: TOTGAI
Unique No: 10736297
Signed: Sean Felton
Report Date: 10 Nov 2023



CONSTRUCTION EQUIPMENT



GRAPHS

