

CONSTRUCTION EQUIPMENT 541 VOLVO L70GLB 614545 - HYDRAULIC SYSTEM



Sample No: VCP411701

Oil Type: MOBIL HYDRAULIC OIL AW 46

Job No: 541

VOLVO	E INFORMATION			
	LINFURMATION		_	
Sample Number		VCP411701		
Sample Date		07 Nov 2023		
Machine Hours		1380		
Oil Hours		0		
Oil Changed		Changed		
Sample Status		NORMAL		
VOLVO				
OIL CON	IDITION			
Visc @ 40°C	cSt	44.4		
Acid Number (Al	V) ma KOH/a	■0.18		
	·,g, g			
VOLVO	MINATION			
	MINATION			
Particles >4µm		1119		
Particles >6µm		■313		
Particles >14µm		■31		
ISO 4406:1999 (c	r)	17/15/12		
Silicon	ppm	6		
Sodium	ppm	0		
Potassium	ppm	1		
VOLVO				
WEAR	METALS			
Iron	ppm	2		
Copper	ppm	2		
Lead	ppm	1		
Tin	ppm	0		
Aluminum	ppm	■ <1		
Chromium	ppm	■0		
Molybdenum	ppm	■0		
Nickel	ppm	■0		
Titanium	ppm	0		
Silver	ppm	0		
Manganese	ppm	■0		
Vanadium	ppm	0		
ADDITI	VES			
Calcium	ppm	292		
Magnesium	ppm	<u> </u>		
Zinc	ppm	■ 594		
Phosphorus	ppm	455		
Barium	ppm	6		
Daniani	Phili	~		



VCES- VOLVO CONSTRUCTION EQUIPMENT

12345 MAPLEVIEW STREET

LAKESIDE, CA US 92040

Contact: Mark Stewart mark.stewart@vcesvolvo.com

T: X: F: X:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:VOLVO4488Unique No:10743360Signed:Wes DavisReport Date:17 Nov 2023

ppm

Boron



CONSTRUCTION EQUIPMENT





GRAPHS

