

Sample No: VCP414471

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: SW-27111-2 CASTLE

SAMPLE	INFORMATION				
Sample Number		VCP414471	VCP387748	VCP348861	
Sample Date		29 Nov 2023	13 Oct 2022	08 Mar 2022	
Machine Hours		25 NOV 2023 2580	1348	827	
Oil Hours		1100	0	1000	
Oil Changed		Changed	Changed	Changed	
		NORMAL	ABNORMAL	SEVERE	
Sample Status		NORWAL	ABNORWAL	SEVERE	
VOLVO					
OIL CON	DITION				
Visc @ 40°C	cSt	164	166	173	
CONTAN	IINATION				
Water	%	■ 0.173	△ 0.792	2.06	
Silicon	ppm	4	1 1	1 1	
Sodium	ppm	■ 3	2	2	
Potassium	ppm	■ 0	0	□ 0	
VOLVO					
WEAR M	ETALS				
Iron	ppm	1 49	8 1	1 01	
Copper	ppm	■3	10	□ 13	
Lead	ppm	0	6	6	
Tin	ppm	0	1	1	
Aluminum	ppm	■<1	2	5	
Chromium	ppm	■<1	1	1	
Molybdenum	ppm	53	2	2	
Nickel	ppm	■ 0	0	0	
Titanium	ppm	0	<1	<1	
Silver	ppm	0	<1	<1	
Manganese	ppm	-<1	2	2	
Vanadium	ppm	0	0	0	
	' '				
VOLVO	IEC				
ADDITIV	F7				
Calcium	ppm	161	■1180	1601	
Magnesium	ppm	■3	■22	■ 25	
Zinc	ppm	102	□490	602	
Phosphorus	ppm	■868	□1149	□1071	
Barium	ppm	■ 0	0	0	
Boron	ppm	■80	■92	□ 64	



ARNOLD MACHINERY COMPANY 2975 WEST 2100 SOUTH SALT LAKE CITY, UT US 84119 Contact: TJ LARK tlark@arnoldmachinery.com

T: (801)972-4000 F: (801)975-9434

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO8770Unique No:10776642Signed:Jonathan HesterReport Date:12 Dec 2023



CONSTRUCTION EQUIPMENT





