



# CONSTRUCTION EQUIPMENT

## SW1027987 DIAMOND VOLVO A40D 60013 - REAR RIGHT FINAL DRIVE



**Sample No:** VCP369191  
**Oil Type:** GEAR OIL SAE 80W90  
**Job No:** SW1027987 DIAMOND



### SAMPLE INFORMATION

Sample Number	<b>VCP369191</b>	VC043197	VC016276	---
Sample Date	<b>20 Dec 2023</b>	14 Mar 2003	20 Aug 2002	---
Machine Hours	<b>4671</b>	2053	1379	---
Oil Hours	<b>0</b>	674	1379	---
Oil Changed	<b>Changed</b>	Not Changd	Changed	---
Sample Status	<b>ABNORMAL</b>	ABNORMAL	ABNORMAL	---

**ARNOLD MACHINERY COMPANY**  
 4323 EAST WINSLOW AVENUE  
 PHOENIX, AZ  
 US 85040  
 Contact: RANDY PRZEKURAT  
 randyp@arnoldmachinery.com  
 T:  
 F: (602)414-1904



### OIL CONDITION

Visc @ 40°C	cSt	<b>▲ 334</b>	140.1	138.1	---
-------------	-----	--------------	-------	-------	-----



### CONTAMINATION

Water	%	<b>NEG</b>	NEG	NEG	---
Silicon	ppm	<b>▲ 103</b>	■ 11	■ 17	---
Sodium	ppm	■ 5	■ 1	■ 2	---
Potassium	ppm	■ 12	■ 10	■ 17	---

### Diagnosis

We advise that you check all areas where dirt can enter the system. The oil change at the time of sampling has been noted. Resample at the next service interval to monitor. Gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress. The oil viscosity is higher than normal. Confirm oil type.



### WEAR METALS

Iron	ppm	<b>▲ 986</b>	■ 338	■ 314	---
Copper	ppm	■ 9	■ 10	■ 16	---
Lead	ppm	■ 0	■ <1	■ 2	---
Tin	ppm	■ 0	■ 1	■ 0	---
Aluminum	ppm	<b>▲ 17</b>	■ <1	■ 3	---
Chromium	ppm	■ 17	■ 5	■ 5	---
Molybdenum	ppm	■ 2	0	0	---
Nickel	ppm	■ 7	■ 3	■ 5	---
Titanium	ppm	2	■ 0	■ <1	---
Silver	ppm	0	■ 0	■ 0	---
Manganese	ppm	■ 14	7	7	---
Vanadium	ppm	0	0	<1	---



### ADDITIVES

Calcium	ppm	■ 111	20	30	---
Magnesium	ppm	■ 15	2	2	---
Zinc	ppm	■ 43	14	16	---
Phosphorus	ppm	■ 1266	616	638	---
Barium	ppm	■ 0	0	1	---
Boron	ppm	■ 174	18	0	---

**Depot:** VOLVO6174  
**Unique No:** 10808690  
**Signed:** Don Baldrige  
**Report Date:** 02 Jan 2024



# CONSTRUCTION EQUIPMENT



## GRAPHS

