

CONSTRUCTION EQUIPMENT 659478 VOLVO A40G 315157 - HYDRAULIC SYSTEM



Sample No: VCP437461

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No: 659478

| SAMPLE INFORMATION | l | | |
|--------------------|-------------|------|--|
| Sample Number | VCP437461 | | |
| Sample Date | 11 Jan 2024 | | |
| Machine Hours | 2059 | | |
| Oil Hours | 0 | | |
| Oil Changed | Not Changd | | |
| Sample Status | NORMAL | | |
| | | | |

| VOLVO | | | | |
|------------------|----------|-------------|------|--|
| OIL CONDI | TION | | | |
| Visc @ 40°C | cSt | 44.7 | | |
| Acid Number (AN) | mg KOH/g | 0.45 | | |
| | | | | |

| VOLVO | | | | | | |
|-------------------|-----|------------|--|--|--|--|
| CONTAMINATION | | | | | | |
| Water | % | NEG | | | | |
| Particles >4µm | | 4845 | | | | |
| Particles >6µm | | 710 | | | | |
| Particles > 14µm | | ■39 | | | | |
| ISO 4406:1999 (c) | | 19/17/12 | | | | |
| Silicon | ppm | ■8 | | | | |
| Sodium | ppm | 1 | | | | |
| Potassium | ppm | ■ 2 | | | | |

| WEAR METALS Iron ppm 4 | THE PARTY OF THE P | | | | |
|--|--|--------|---------------|------|--|
| Copper ppm 2 <th>WEAR</th> <th>METALS</th> <th></th> <th></th> <th></th> | WEAR | METALS | | | |
| Lead ppm 2 Tin ppm <1 | Iron | ppm | 4 | | |
| Tin ppm <td>Copper</td> <td>ppm</td> <td>2</td> <td> </td> <td></td> | Copper | ppm | 2 | | |
| Aluminum ppm 2 Chromium ppm 0 Molybdenum ppm 0 Nickel ppm 0 Titanium ppm 0 Silver ppm 0 Manganese ppm <1 | Lead | ppm | 2 | | |
| Chromium ppm 0 Molybdenum ppm 0 Nickel ppm 0 Titanium ppm 0 Silver ppm 0 Manganese ppm | Tin | ppm | ■<1 | | |
| Molybdenum ppm 0 Nickel ppm 0 Titanium ppm 0 Silver ppm 0 Manganese ppm <1 | Aluminum | ppm | 2 | | |
| Nickel ppm 0 Titanium ppm 0 Silver ppm 0 Manganese ppm <1 | Chromium | ppm | ■ 0 | | |
| Titanium ppm 0 Silver ppm 0 Manganese ppm < 1 | Molybdenum | ppm | ■ 0 | | |
| Silver ppm 0 Manganese ppm ■ <1 | Nickel | ppm | ■ 0 | | |
| Manganese ppm | Titanium | ppm | 0 | | |
| | Silver | ppm | 0 | | |
| Vanadium ppm 0 | Manganese | ppm | ■ <1 | | |
| | Vanadium | ppm | 0 | | |

| ADDITI | IVES | | | |
|------------|------|------------|------|--|
| Calcium | ppm | 166 | | |
| Magnesium | ppm | ■7 | | |
| Zinc | ppm | 455 | | |
| Phosphorus | ppm | ■358 | | |
| Barium | ppm | ■ 0 | | |
| Boron | ppm | 2 | | |



JON M HALL COMPANY

1920 BOOTHE CIRCLE SUITE 110 LONGWOOD, FL US 32750

Contact: SERVICE MANAGER

T: (407)215-0410 F:

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:JONLONUnique No:10835620Signed:Wes DavisReport Date:19 Jan 2024



CONSTRUCTION EQUIPMENT





GRAPHS

