

CONSTRUCTION EQUIPMENT

SW-28378-2 CMC ROCK VOLVO EC480EL 315023 - REAR LEFT FINAL DRIV

Sample No: VCP412545

Oil Type: VOLVO PREMIUM GEAR OIL 80W-90 GL-5

Job No: SW-28378-2 CMC ROCK

	NFORMATIO	DN _					
Sample Number		VCP412545	VCP406300				
Sample Date		04 Jan 2024	08 Apr 2023				
Machine Hours		2330	621				
Oil Hours		2330	0				
Oil Changed		Changed	N/A				
Sample Status		NORMAL	NORMAL				
VOLVO							
OIL CONDI	IIIUN						
Visc @ 40°C	cSt	167	171		²		
CONTAMI	NATION						
Water	%	NEG	NEG				
Silicon	ppm	61	6 9				
Sodium	ppm	4	4				
Potassium	ppm	■ 4	4				

WEAR METALS						
Iron	ppm	1211	■379			
Copper	ppm	1	- <1			
Lead	ppm	■<1	0			
Tin	ppm	■<1	0			
Aluminum	ppm	13	1 6			
Chromium	ppm	12	7			
Molybdenum	ppm	2	1			
Nickel	ppm	■ <1	<1			
Titanium	ppm	■<1	1			
Silver	ppm	0	0			
Manganese	ppm	10	6			
Vanadium	ppm	<1	0			

ADDITIVES							
Calcium	ppm	71	□108				
Magnesium	ppm	10	1 3				
Zinc	ppm	■31	1 9				
Phosphorus	ppm	697	■287				
Barium	ppm	4	5				
Boron	ppm	67	- <1				



ARNOLD MACHINERY COMPANY 2975 WEST 2100 SOUTH

29/5 WEST 2100 SOUTH

SALT LAKE CITY, UT

US 84119

Contact: TONY PAYAN

tpayan@arnoldmachinery.com

T: (801)972-4000 F: (801)975-9434

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The condition of the oil is acceptable for the time in service.

Depot:VOLVO8770Unique No:10836574Signed:Wes DavisReport Date:19 Jan 2024



CONSTRUCTION EQUIPMENT





