

CONSTRUCTION EQUIPMENT VOLVO A45G 352638 - HYDRAULIC SYSTEM



Sample No: VCP441088

Oil Type: VOLVO SUPER HYDRAULIC OIL 46

Job No:

SAMPLE IN	NFORMATION				
Sample Number		VCP441088			
Sample Date		09 Feb 2024			
Machine Hours		4358			
Oil Hours		0			
Oil Changed		Changed			
Sample Status		NORMAL			
Sumple Status		110111111111			
VOLVO	TION				
OIT CONDI.	IIUN				
Visc @ 40°C	cSt	45.8			
Acid Number (AN)	mg KOH/g	■ 0.44			
CONTAMINATION					
Water	%	NEG			
Particles >4µm	70	2309			
Particles >6µm		2309 ■249			
Particles > 14µm		6			
ISO 4406:1999 (c)		18/15/10			
Silicon	nnm	■ 14			
Sodium	ppm	1			
Potassium	ppm	2			
1 Otassiaiii	ррш				
VOLVO					
WEAR ME	TALS				
Iron	ppm	■ 5			
Copper	ppm	2			
Lead	ppm	■ 3			
Tin	ppm	■<1			
Aluminum	ppm	■ 7			
Chromium	ppm	■<1			
Molybdenum	ppm	■0			
Nickel	ppm	■ 0			
Titanium	ppm	<1			
Silver	ppm	0			
Manganese	ppm				
Vanadium	ppm	0			
VOLVO					
ADDITION					
Calcium	ppm	■331			
Magnesium	ppm	2			
Zinc	ppm	498			
Phosphorus	ppm	■381			
Barium	ppm	■0			
Boron	ppm	■0			
	F P				



ALTA EQUIPMENT COMPANY

5151 DR MARTIN LUTHER KING BLVD FORT MYERS, FL US 33905 Contact: TODD LARK tlark@altaequipfl.com

T:

F: (239)481-3302

Diagnosis

Resample at the next service interval to monitor. All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Depot:VOLVO0090Unique No:10875563Signed:Wes DavisReport Date:14 Feb 2024



CONSTRUCTION EQUIPMENT





GRAPHS

