

CONSTRUCTION EQUIPMENT VOLVO EC350EL 314338 - LEFT FINAL DRIVE



Sample No: VCP442928

Oil Type: GEAR OIL SAE 80W90

Job No:

SAMPLI	E INFORMATIO	N		
Sample Number		VCP442928	 	
Sample Date		14 Feb 2024	 	
Machine Hours		2027	 	
Oil Hours		0	 	
Oil Changed		N/A	 	
Sample Status		SEVERE	 	
VOLVO	IDITION			
OIL CON	IDITION			
Visc @ 40°C	cSt	294	 	
CONTAI	MINATION			
Water	%	0.382	 	
Silicon		4528	 	
Sodium	ppm	•	 	
	ppm	■ 87	 	
Potassium	ppm	■170	 	
VOLVO				
WEAR	METALS			
Iron	ppm	9836	 	
Copper	ppm	■ 15	 	
Lead	ppm	- <1	 	
Tin	ppm	<u> </u>	 	
Aluminum	ppm	▲ 681	 	
Chromium	ppm	120	 	
Molybdenum	ppm	1 6	 	
Nickel	ppm	<u> </u>	 	
Titanium	ppm	■ 59	 	
Silver	ppm	0	 	
Manganese	ppm	■80	 	
Vanadium	ppm	2	 	
ADDITI	VEC			
_				
Calcium	ppm	■99	 	
Magnesium	ppm	110	 	
Zinc	ppm	12	 	
Phosphorus	ppm	■274	 	
Barium	ppm	11	 	
Boron	ppm	1	 	



SCOTT EQUIPMENT COMPANY LLC - Lake Charles
PO BOX 16955
LAKE CHARLES, LA
US 70616
Contact: TINA LEDOUX
tledoux@scottcompanies.com
T: (337)433-9811
F: (318)433-6623

Diagnosis

We advise that you check all areas where dirt can enter the system. We advise that you check for the source of water entry. We recommend that you drain the oil from the component if this has not already been done. We advise that you inspect for the source(s) of wear. We recommend an early resample to monitor this condition.Gear wear is indicated. Elemental levels of silicon (Si) and aluminum (Al) indicate aluminasilicate (coarse dirt) ingress. There is a moderate concentration of water present in the oil. The oil is no longer serviceable due to the presence of contaminants.

Depot:VOLVO6244Unique No:10887353Signed:Sean FeltonReport Date:22 Feb 2024



CONSTRUCTION EQUIPMENT





